Form 9-331 a (Feb. 1951)

ı				
ı				
ı				
Į				
i				
ı				- -
1		İ	1	1
ı		1	ł	1
1		ļ. 		. -
			ļ	:
		i	!	•

(SUBMIT IN TRIPLICATE)

UNITED STATES DEPARTMENT OF THE INTERIOR **GEOLOGICAL SURVEY**

Bud App	ger Bureau No. 42-R358.4. roval expires 12-31-60.
Land Office	Santa Fe
Lease No	078416-A
Unit	Wilch

	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OF BEPAIR
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL	<u> </u>
(INDICATE ABOVE BY CHECK MARK NAT	TURE OF REPORT, NOTICE, OR OTHER DATA) 11. S. CSCLOPICAL TATMORETED 1.19 December 6, 19
Wilch Vell No. 1-25 is located 795 ft. from NE 1/4 Section 26 T-29-N R-6 (Kan) (Kan)	B-W NMPM
Basin Dakota San Ju	an Non Marie 1
(1100)	, Dra
he elevation of the derrick floor above sea level	is 6340 ft. UEC 1 0 1967
	OF WORK
	· · · · · · · · · · · · · · · · · · ·
	valents, and langing of proposed casings; indicate medging joos, ce
and a second a second and a second a second and a second	nd ran 240 joints of 4-1/2" 10.50# J-
ell drilled to T.D. of 7550', logged as asing landed 7525' w/370 sx Class A can all of the state	nd ran 240 joints of 4-1/2" 10.50# J-ment, 16% Gel, 6.25# Gilsonite, 4/10 of A cement, 4% Gel, 1/4# Flocele per silog indicated top cement at 4340° coverant at 4340° coverant at 5390, 5330, 5270, 5210,
ell drilled to T.D. of 7550', logged as asing landed 7525' w/370 sx Class A cer. % of HR7 added followed w/250 sx Class /10 of 1% Haled 9 added. Cement Bond lessaverde section. Ten BW Hyflo guides 1090, 5030, 4970, 4910 & 4850'. Two class waiting on completion rig. I understand that this plan of work must receive approval in writh the company waiting on Delhi-Taylor Oil Corr. Address PaO. Drawer 1198	nd ran 240 joints of 4-1/2" 10.50# J-ment, 16% Gel, 6.25# Gilsonite, 4/10 of A cement, 4% Gel, 1/4# Flocele per silog indicated top cement at 4340° covid installed at 5390, 5330, 5270, 5210, cose tolerance cement baskets at 4910 of the company of the Geological Survey before operations may be commence coration Original signed by
asing landed 7525' w/370 ax Class A cer % of HR7 added followed w/250 ax Class /10 of 1% Haled 9 added. Cement Bond esaverde section. Ten BW Hyflc guides 090, 5030, 4970, 4910 & 4850'. Two clow waiting on completion rig. I understand that this plan of work must receive approval in writh the company was p	nd ran 240 joints of 4-1/2" 10.50# J-ment, 16% Gel, 6.25# Gilsonite, 4/10 of A cement, 4% Gel, 1/4# Flocele per silog indicated top cement at 4340' cover installed at 5390, 5330, 5270, 5210, cose tolerance cement baskets at 4910 of the commence poration Original signed by A. R. Gibson A. R. Gibson
all drilled to T.D. of 7550', logged as using landed 7525' w/370 ax Class A cert of HR7 added followed w/250 ax Class /10 of 1% Haled 9 added. Cement Bond esaverde section. Ten BW Hyflo guides 090, 5030, 4970, 4910 & 4850'. Two clow waiting on completion rig. I understand that this plan of work must receive approval in writed the company Delhi-Taylor Oil Corpudding Section 1980.	nd ran 240 joints of 4-1/2" 10.50# J-ment, 16% Gel, 6.25# Gilsonite, 4/10 of A cement, 4% Gel, 1/4# Flocele per silog indicated top cement at 4340° covid installed at 5390, 5330, 5270, 5210, cose tolerance cement baskets at 4910 of the company of the Geological Survey before operations may be commence coration Original signed by