

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☒ OTHER	7. UNIT AGREEMENT NAME
2. NAME OF OPERATOR El Paso Natural Gas Company	8. FARM OR LEASE NAME Hughes
3. ADDRESS OF OPERATOR Box 990, Farmington, New Mexico	9. WELL NO. 5 (CWC)
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 990'S, 1650'W	10. FIELD AND POOL, OR WILDCAT Blanco Mesa Verde
14. PERMIT NO.	11. SEC., T., E., M., OR BLK. AND SURVEY OR AREA Sec. 21, T-29-N, R-6-W
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 6435' GL	12. COUNTY OR PARISH N.M.P.M.
	13. STATE San Juan New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) **Squeeze**

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

On 11-2-66 cut stuck tubing at 4703', still stuck, cut at 4636', tubing still stuck and cut at 4500'. Pulled 1500# pressure on annulus and tubing came free, pulled tubing, perf. 4 squeeze holes at 4420', set cement retainer at 4398', pressured up to 2000# on annulus and could not pump down tubing with 6000#. Spotted 25 sacks Class "A" cement w/15% sand and .75% TIC on top of retainer and filled to 4275'.

11-3-66 Perf squeeze holes in 7" casing at 2150'. Set cement retainer at 2033', squeezed thru perfs w/75 sacks cement w/15% sand and 3/4 of 1% TIC, 2% calcium chloride, followed by 100 sacks Class "A" cement, 3% calcium chloride, final pump pressure 700#, held 500#.

RECEIVED

NOV 7 1966

U. S. GEOLOGICAL SURVEY
FARMINGTON, N. M.

18. I hereby certify that the foregoing is true and correct

SIGNED

Original signed by
Carl E. MatthewsTITLE **Petroleum Engineer**DATE **11-4-66**

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

*See Instructions on Reverse Side



Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, are contained in the instructions, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 1: There are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 2: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth-top top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

U.S. GOVERNMENT PRINTING OFFICE: 1967-O-385229

507-1-11

RECEIVED

APR 1 1968

U.S. GOVERNMENT PRINTING OFFICE

RECEIVED

APR 1 1968