

TENNECO OIL COMPANY
DURANGO DISTRICT
FLORENCE #31
890' FNL-890' FEL
Sec. 12-29 N-8 W
GL 6273
KB 12'



DUAL COMPLETION:
BLANCO MESAVERDE
BASIN DAKOTA

PERFORATIONS
(GRC MEASURE)

MESAVERDE PERFORATIONS

- 4 H.P.F. 4750-51
4765-66
4778-79
4797-98
4817-18
4850-51
4919-20
4935-36
4986-87
5006-07
5143-44
5214-15
5226-27
5235-36
5245-46
5258-59
5275-76
5294-95
5327-28
5341-42

DAKOTA PERFORATIONS

- 4 H.P.F. 7327-28
7332-33
7404-05
7407-08
7436-37
7437-38
7457-58
7484-85
7515-16
7536-37

10 3/4" CSG. AT 181'

BOWEN CSG. PATCH AT 300'

STAGE COLLAR AT 4470'

7" OD CSG. AT 4720'

2 3/8" EUE J-55 TBG (233 JTS 7253.42')

STAGE COLLAR AT 5454'

SLIDING SLEEVE AT 7267'

"F" LDG. NIPPLE AT 7274'

BAKER MOD. D PKR. AT 7275'

CEMENTING RECORD

- 1st Stage: CMTED w/100 sx class C
50-50 POZMIX top at 6800'
2nd Stage: CMTED w/175 sx class C
50-50 POZMIX top at 4470'
3rd Stage: CMTED w/270 sx class C
top at 1850'
4th Stage: CMTED w/140 sx class C
top at surface.

PBTD

4 1/2" O.D. CSG. AT 7555'

PBTD — 7538'

TD — 7555'