

Delhi-Taylor Oil Corp.
 No. 2-30 Florence
 Location: 870' F/S.L. 830' F/WL
 Sec. 1, T29N-R8W.
 San Juan County, New Mexico

Blanco Mesaverde
 Basin Dakota

PERFORATIONS:

(LANE WELLS PFC Measure)

Mesaverde Perts w/1 jet hole
 at each depth listed.

4803'	4972'	5291'
4812'	4979'	
4816'		5307'
4922'	5153'	5311'
4830'	5159'	5315'
4834'		5326'
4839'	5225'	5339'
4846'	5227'	
4852'	5231'	
4857'	5257'	
4883'	5267'	
4987'	5271'	
4898'	5276'	

Dakota Perts w/2 jets per ft.

7414' - 7436
 7559 1/2' - 7569 1/2'
 7587' - 7588'
 7592' - 7598
 7605' - 7608'
 7611' - 7615'
 7628' - 7629'
 7634' - 7639'

2.375" O.D.
 1.995" I.D.


10 3/4" Csg @ 137'

Tubing lost points at the
 following depths (Lane Wells
 PFC 100.)

5319.73 - 5288.24
 5250.85 - 5219.95
 5179.19 - 5148.20
 4992.86 - 4961.35
 4900.02 - 4869.50
 4827.55 - 4797.14
 4858.53 - 4827.55
 5351.24 - 5319.73
 5282.34 - 5250.85

7" Csg @ 4700'

Side tracked @ 4714'



2 3/8" EUE O.D. TYPE L
 S.H.G. sleeve.

2 3/8" Type S L3: Grip
 Nipple.

2 3/8" Hq. L3: Tee 3
 7364.40'

Baker Model "DA"
 Retainer Production
 Packer w/ Baker
 latching type
 tubing seal asse-
 mly @ 7366 - 7372'
 Lane Wells wire
 line measure.

4 1/2" csg @ 7756'

T.D. 7773'

Feb 6-62