



(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office Santa Fe
Lease No. SF 078487-B
Unit Prichard Federal
DBM-3-B

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL	<u>Dual Complete</u>

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

CORRECTED REPORT

January 2, 19 59

Well No. 1 (Pictured Cliffs) is located 1650 ft. from N line and 1650 ft. from E line of sec. 6
SW/4 Sec. 6 (Twp.) 29N (Range) 10W (Meridian)
wildcat (Field) San Juan (County or Subdivision) New Mexico (State or Territory)

The elevation of the derrick floor above sea level is 6260 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudlogging jobs, cementing points, and all other important proposed work)

Set plug choke. Pulled tbg. Set Baker Model "D" production packer @ 2975. Ran DR packer plug. Tested 7" casing and packer 2800# OK. Perforated 2 bullets per ft 2919-2959, GR measurements. Tested Pictured Cliffs natural 200 MCF/D. Treated well w/ 20,000# 20-40 sand; 20,000# 10-20 sand; 36,000 gallons water. BHP 1250-800. Mx tr pr 800, min tr pr. 400. Injection rate 41.8 bbl/min. Cleaned out after frac. Recovered DR packer plug. Ran 2-3/8" and 2-7/8" tbg w/ Baker seal nipples. Locator sub, tubing perforations @ 5025-28. Ran 1" OD 1.315# J-55 tbg, set @ 2937. 1" tbg. perforations @ 2937-2925. Attempted to recover plug choke in 2-3/8" tbg. failed to recover. Perforated 2-3/8" tubing 5019-24 w/ 15 bullets. Shut-in pressure Pictured Cliffs, 974#. Shut-in pressure Mesaverde, 810#. Opened casing (Pictured Cliffs) for 3 hr. on 3/4" choke. Volume at end of 3 hrs, 2730 MCF/day. CAGP 4760 MCF/day. Recompletion started 12/17/58, complete 12/28/58.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company ANDERSON-PRICHARD OIL CORPORATION

Address 1740 Broadway - Suite B-400

Denver 2, Colorado

By

Title District Superintendent