

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other

2. NAME OF OPERATOR
El Paso Natural Gas Company

3. ADDRESS OF OPERATOR
P.O. Box 289, Farmington, New Mexico 87401

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1786'N, 850'W
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

SUBSEQUENT REPORT OF:

☒
☒
☐
☐
☐
☐
☐
☐

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

5. LEASE
SF 078945
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
San Juan 29-7 Unit
8. FARM OR LEASE NAME
San Juan 29-7 Unit
9. WELL NO.
76A
10. FIELD OR WILDCAT NAME
Blanco M.V.
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 18, T-29-N, R-7-W
N.M.P.M.
12. COUNTY OR PARISH
Rio Arriba
13. STATE
New Mexico
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)
6836' GL

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

11-03-78: TD 3990'. Ran 99 jts. 7", 20#, K-55 intermediate casing, 3978' set at 3990'. Cemented w/323 cu. ft. cement. WOC 12 hours; held 1200#/30 minutes. Top of cement at 3200'.

11-06-78: TD 6193'. Ran 65 jts. 4 1/2", 10.5#, K-55 casing liner, 2388' set 3805-6193'. Float collar set at 6178'. Cemented w/425 cu. ft. cement. WOC 18 hours.

04-22-79: PBTD 6178'. Tested casing to 3500#, OK. Perfed Upper & Lower P.L. 5746, 5752, 5758, 5765, 5771, 5776, 5783, 5792, 5800, 5808, 5833, 5842, 5854, 5862, 5882, 5898, 5924, 5940, 5962, 6000, 6007, 6026, 6042, 6058, 6088, 6096, 6138, 6159' w/1 SPZ. Fraced w/104,000# 20/40 sand and 197,000 gal. water. Flushed w/7700 gal. water.

(OVER)

Subsurface Safety Valve: Manu. and Type

Set @ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED A. G. Busco TITLE Drilling Clerk DATE April 24, 1979

(This space for Federal or State office use)

APPROVED BY W. J. [illegible] TITLE Drilling Clerk DATE April 24, 1979
CONDITIONS OF APPROVAL, IF ANY:

04-22-79: BELLING C.H. & SONS 2081' 2305' 2312' 2332'

*See Instructions on Reverse Side



