Form	9-331
(May	1963)

16.

UNITED STATES SUBMIT IN TRIPLICATE. DEPARTMENT OF THE INTERIOR (Other Interior verse side)

Instructions on re-

Form approved. Budget Bureau No. 42-R1424. 5. LEASE DESIGNATION AND SERIAL NO.

GEOLOGICAL	SURVEY

	SU	NDR	Y NO	TICES	A١	۷D	REPC	ORTS	ON	W	ELLS	
Do not	use thi	s form	for proj	posals to	drill	or to	deepen	or plug	back	a o	different	reservoir.

	ы	175	150	12 - 1	Δ				
6. Y	ł. J	861.	KN,	YLLO	TTEE	OR	TRIBE	NAN	1 E

(Do not use this form for proposa Use "APPLICA"	ls to drill or to deepen or plus NON FOR PERMIT—" for such	g back to a different reservoir. a proposals.)		
OIL GAS X OTHER			7. UNIT AGREEMENT NA	ME
2. NAME OF OPERATOR		- Control of the Cont	8. FARM OR LEASE NAM	E
El Paso Natural Gas Com	oany		Vandewart	
3. ADDRESS OF OPERATOR		/85XXX	9. WELL NO.	
P. O. Box 990, Farmingto	on, NM 87401	(1)	1-A	·
4. LOCATION OF WELL (Report location cle See also space 17 below.) At surface	arly and in accordance with a	ny St. 12 regularements.	Blanco Mesa	Verde
1535'N, 1100'W		Milit CONT. 3	Sec. 12, T-2 N.M.P.M.	
14. PERMIT NO.	15. ELEVATIONS (Show whether	DF, RT, GR, etc.)	12. COUNTY OR PARISH	13. STATE
	6250' GL		San Juan	New Mexico

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

		* * * *				
NOTICE OF INTENTION TO:			SUBSEQUENT REPORT OF:			
TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE		PULL OR ALTER CASING MULTIPLE COMPLETE ABANDON*		WATER SHUT-OFF FRACTURE TREATMENT SHOOTING OR ACIDIZING (Other)	REPAIRING WELL ALTERING CASING ABANDONMENT®	
REPAIR WELL (Other)	L	CHANGE PLANS		(Note: Report results of mult Completion or Recompletion Re	tiple completion on Welleport and Log form.)	i

- 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*
 - 02-01-75 TD 3293'. Ran 83 joints 7", 20#, J-55 intermediate casing, 3281' set at 3293'. Cemented with 293 cu. ft. cement. WOC 12 hours, held 1200#/30 minutes. Top of cement at 2075'.
 - TD 5550'. Ran 60 joints 4 1/2", 10.5#, J-55 casing liner, 2397' set from 3153' to 5550'. Float collar set at 5533'. Cemented with 420 cu. ft. cement. WOC 18 hours.
 - PBTD 5533'. Tested casing to 4000#, OK. Perf'd Point Lookout 5182', 5200', 5216', 5242', 5258', 5288', 5310', 5329', 5346', 5364', 5388', 5410', 5452', 02-25-75 and 5478' with 1 shot per zone. Frac'd with 115,000#--20/40 sand and 119,160 gal treated water. No balls drops. Flushed with 7400 gallons water.
 - 02-26-75 Perf'd Cliff House 4646', 4664', 4718', 4734', 4750', 4766', and 4782' with 1 shot per zone. Frac'd with 55,000#--20/40 sand and 61,800 gallons treated water. No ball drops. Flushed with 6700 gallons water.

8. I hereby certify that the foregoing is true and correct SIGNED	TITLE	Drilling Clerk	DATE	February 27, 1975
(This space for Federal or State office use)				
APPROVED BYCONDITIONS OF APPROVAL, IF ANY:	TITLE		DATE	