SUBMIT IN TRIPLICATE.

(Other instructions on reverse side)

	approved		
Budget	Bureau	No.	42-R1425.

UNITED STATES DEPARTMENT OF THE INTERIOR

50-045-2389 5. LEASE DESIGNATION AND SERIAL NO. GEOLOGICAL SURVEY SF-078046 6. IF INDIAN, ALLOTTEE OR TRIBE NAME APPLICATION FOR PERMIT TO DRILL, DEEPEN, OR PLUG BACK 1a. TYPE OF WORK 7. UNIT AGREEMENT NAME DRILL X DEEPEN | PLUG BACK 🗌 b. TYPE OF WELL WELL MULTIPLE WELL X SINGLE ZONE 8. FARM OR LEASE NAME OTHER ZONE 2. NAME OF OPERATOR Hughes Tenneco Oil Company 9. WELL NO. 3. ADDRESS OF OPERATOR #5 720 South Colorado Blvd., Denver, Colorado 80222 10. FIELD AND POOL, OR WILDCAT 4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*)
At surface Basin Dakota 11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA 965' FNL, 1,540' FWL At proposed prod. zone Sec. 20, T29N-R8W 14. DISTANCE IN MILES AND DIRECTION FROM NEAREST TOWN OR POST OFFICE. 12. COUNTY OR PARISH | 13. STATE See Point 1B, Surface Use Plan San Juan New Mexico 16. DISTANCE FROM PROPUSED*
LOCATION TO NEAREST
PROPERTY OR LEASE LINE, FT.
(Also to nearest drig, unit line, if any)
15. DISTANCE FROM PROPOSED LOCATION*
TO NEAREST WELL, DRILLING, COMPLETED,
OR APPLIED FOR, ON THIS LEASE, FT. NO. OF ACRES ASSIGNED TO THIS WELL 16. NO. OF ACRES IN LEASE 320 19. PROPOSED DEPTH 20. ROTARY OR CABLE TOOLS 7,720' Rotary 21. ELEVATIONS (Show whether DF, RT, GR, etc.) 22. APPROX. DATE WORK WILL START* 6,470' G.L. February 1, 1980 $\overline{23}$. PROPOSED CASING AND CEMENTING PROGRAM SIZE OF HOLE SIZE OF CASING WEIGHT PER FOOT SETTING DEPTH QUANTITY OF CEMENT 9-5/8" 13-3/4" 250' 36# Sufficient to circulate to surfa 7-7/8" 4-1/2" 10.5#, 11.6# 7,720 Sufficient to circulate to surfa SEE ATTACHED SHEET gas not ledicated U. S. GEOLOGICAL SURVEY FARM NOTON, N. M. IN ABOVE SPACE DESCRIBE PROFOSED PROGRAM: If proposal is to deepen or plug back, give data on present productive zon zore. If proposal is to drill or deepen directionally, give pertinent data on subsurface locations and measured and true wout preventer program, if any. 24 Division Production Manager September 4, 1979 TITLE (This space for Federal or State office use)

oh Frak

CONDITIONS OF APPROVAL, IF ANY

PERMIT NO.

APPROVED BY

*See Instructions On Reverse Side

TITLE

NMOCC

APPROVAL DATE

DATE _

OIL CONSERVATION DIVISION

STATE OF NEW MEXICO ENERGY AND MINERALS DEPARTMENT

P. O. BOX 2088 SANTA FE, NEW MEXICO 87501

Form C-102 Revised 10-1-78

All distances must be from the cuter boundaries of the Section.

			1.				T	
Operator TENNECO OI	T. COMPANY		Lease	JOHES			Well No.	
Unit Letter	Section	Township	Rong		County			
С	20	29N		3W	San J	luan		
Actual Footage Loc	37	+h	151.0			T.T		
Ground Level Elev.	 ,	orth line	and 1540	fee	t from the	West	line Dedicated Acres	tge:
6470	Dakota		Basir	n Dakota				320 Acres
1. Outline th		ted to the subject			r hachure	marks on th	e plat below.	
	han one lease is nd royalty).	dedicated to the	well, outline	each and ide	ntify the o	ownership th	ereof (both as	s to working
3. If more than one lease of different ownership is dedicated to the well, have the interests of all owners been consolidated by communitization, unitization, force-pooling.etc?								een consoli-
Yes	X No If a	nswer is "yes;" ty	pe of consoli	dation	· <u></u>			
		owners and tract d	lescriptions v	which have ac	tually be	en consolida	ited. (Use rev	erse side of
	if necessary.)	ed to the well until	l all internati	. h h	1: 3	.] (1	****	•
		or until a non-star						
sion.						-, 2001.	approved by v	
វិណាពាពា	unnindamm						CERTIFICATION	2N
	i	E			j		CERTITICATI	
	1-2					I hereby o	ertify that the in	formation con-
	1 %			· I		tained her	ein is true and c	omplete to the
1540'	1					best of my	knowledge and i	belief.
E 1940	 							
1540'	 			 		Norpe	Pull	
	i	Ē				Position	1) Mar 50	1
티	1			<u> </u>		Enviro	nmental C	cordinato
	•			, 1		Company	- 041 a	
	i			· ·	1	Date	Oil Com	ipany
	CONPCO S	\^ I=		!		August	31, 1979	, .
Ēļ			- 205	1				
TE.	NNECO OIL CO). E 20				1 6		
	1		/ ENGLY			1	certify that the this plat was plo	
	SF-078046	E 1	SEPO	1979		1	actual surveys n	. i
	1	Ė	LOU CON	1000		1	supervision, and	ŀ
	i	Ē	1012.3			İ	nd correct to th	e best of my
	+			! _ <i>_</i>		knowledge	and belief.	
3	i — — —			l I				
TE	i					Date Survey	ed corn	LAND
	l	E				July 1		Stall
<u> </u>	i					Registered F and/or Land	rofe stonel Eng. Surveyor	meero F
3	i	E		 		Fred	BXXEL	50/1
	<u> </u>			! !		Fred B	. Kerr Jr.	1EXIC
	dan daman	minini.	-			Certificate 1	10. 8. K	ERR, IR.
0 330 660	90 1320 1650 198	0 2310 2640	2000 1500	1000 5	00 0	3750		THE PARTY NAMED IN COLUMN TWO IS NOT THE PARTY N

HUGHES #5

1. The geological name of the surface formation is Tertiary San Jose

283. Estimated Formation Tops:

Ojo	1900'	Mancos	5566 '
Pictured Cliffs	3050'	Gallup	6646' ·
Cliffhouse	4823'	Greenhorn	7380'
Menefee	4891'	Dakota A	7471'
Point Lookout	5619'	Total Depth	7720'

- 4. Drill a 13 3/4" hole to 300⁺. Run 9 5/8", 36#, K-55 ST&C casing to 300⁺ and circulate cement to surface using 2% CaCl₂ in cement. Drill out shoe and reduce hole to 8 3/4". Drill 8 3/4" hole to 3500⁺. Run 7", 23#, K-55 ST&C casing to 3500⁺ and circulate cement to surface. Drill out of 7" with 6 1/4" bit using gas as circulating fluid. Drill to total depth.. If productive, run 4 1/2" casing. Cement in one stage and bring cement to above Mesaverde Zone. If nonproductive, P&A as per U.S.G.S. requirements
- 5. Blowout Preventors:
 Hydraulic double ram, 10". One set of rams will be provided each size drill pipe in the hole. One set of blind rams at all times. Fill line will be 2", kill line will be 2", choke relief line will be 2". BOP's, drills, and tests will be recorded in the driller's log. BOP will be tested every 24 hours and recorded in IADC log.
- 6. Mud Program: (Sufficient quantity of mud and weight material will be available on location.)

```
0-300-
300-3500-
3500-T.D. Spud mud.
Low solids fresh water mud. No WL control.
```

7. Auxiliary Equipment:

- a. Kelly cock will be in use at all times.
- b. Stabbing valve to fit drill pipe will be present on floor at all times.
- c. Mud monitoring will be visual. No abnormal pressures are anticipated.
- d. Floats at bits.
- e. Drill string safety valve(s) to fit all pipe in drill string will be maintained on the rig floor while drilling operations are in progress.
- 8. Coring, Logging, and Testing Program:

No cores will be taken. Samples will be taken as directed by wellsite geological engineer. GR/FDC/CNL caliper from T.D. to base of Mesaverde. GR/SP/SN induction from T.D. to surface casing.

- 9. No abnormal pressures or temperatures are anticipated.
- 10. The drilling of this well will take approximately 10 days.
- ll. Your office (telephone) will be notified of spudding in sufficient time to witness cementing operations. Immediate notice will be given on blowouts, fires, spills, and accidents involving life threatening injuries or loss of life. Prior approval will be obtained before appreciably changing drilling program or commencing plugging operations, plug back work, casing repair work or corrective cementing operations.

1. Existing Roads

- A. Proposed Well Site Location: The proposed wellsite location was surveyed and staked by a registered land surveyor and is located 965' FNL and 1540'FWL, Sec. 20, T29N-R8W, San Juan County, New Mexico. (See Exhibit I acreage dedication plan)
- B. Planned Access Route: The planned access route begins in Blanco, New Mexico and proceeds east on Highway 64 approximately 7 3/4 miles. Turn southwest on dirt road and proceed for approximately 1 1/2 miles to junction in road and turn southeast for 1/4 mile into wellsite location.
- C. Access Road Labelled:

Color Code: Red - Improved Surface Blue - New Access Road

- D. Not applicable the proposed well is a development well.
- E. The proposed well is a development well. See Exhibit for existing roads within a one mile radius.
- F. Existing Road Maintenance or Improvement Plan: The existing roads will require minimal maintenance.

2. Planned Access Roads

(All roads are existing roads.)

- A. Width:
 The average width of the road is twenty feet.
- B. Maximum Grades:

The maximum grades will be 6%.

- C. Turnouts: There are no turnouts planned as sight distance is sufficient.
- D. Drainage Design: The road is center crowned to allow drainage. The road is flat primarily.
- E. Culverts Use Major Cuts and Fills:

No culverts or major cuts and fills will be required.

F. Surfacing Material:
Native soil has been wetted, bladed and compacted to make the road surface, which is existing.

2. Planned Access Roads (Cont'd)

- Gates, Cattleguards, Fence Cuts: No gates, cattleguards or fences will be needed.
- Η. New Roads Centerlined Flagged: Existing Roads.
- 3. Location of Existing Wells

The proposed well is a development well. ExhibitIII shows existing wells within a one mile radius.

- Α. Water Wells: None
- В. Abandoned Wells: None.
- С. Temporarily Abandoned Wells: None
- D. Disposal Wells: None
- Drilling Wells: See Exhibit III
 Producing Wells: See ExhibitIII E.
- F.
- Shut-In Wells: G. None
- Injection Wells: None Н.
- Ι. Monitoring or Observation Wells: None.
- 4. Location of Existing and/or Proposed Facilities
 - Existing facilities within one mile owned or controlled Α. by Lessee/Operator:
 - Tank batteries -None
 - Production facilities See Exhibit III
 - (2) (3) Oil Gathering Lines - None
 - (4) Gas Gathering Lines -None
 - (5) Injection Lines -None
 - (6) Disposal Lines -None

- В. New facilities in the event of production:
 - (1) New facilities will be within the dimensions of the drill pad. Dimensions are shown on Exhibit IV
 - (3) Construction Materials/Methods: Construction materials will be native to the site. Facilities will consist of a well pad.
 - (4) Protection of Wildlife/Livestock:

Facilities will be fenced as needed to protect wildlife or livestock.

4. Location of Existing and/or Proposed Facilities (Cont'd)

- B. New facilities in the event of production: (cont'd)
 - (5) New facilities will consist of a wellhead, tank and production unit.
- C. Rehabilitation of Disturbed Areas:
 Following the completion of construction, those areas required for continued production will be graded to provide drainage and minimize erosion. Those areas unnecessary for use will be graded to blend with surrounding topography per BLM recommendations.

5. Location and Type of Water Supply

- A. Location and type of water supply:
 Water will be hauled from a private source.
- B. Water Transportation System: Water trucks will be used.
- C. Water wells: N/A.

6. Source of Construction Materials

- A. Materials:
 Construction materials will consist of soil native to the site. Any topsoil, if present, will be stripped and stockpiled as needed.
- B. Land Ownership;
 The planned site and access road is on federal land administered by the Bureau of Land Management.
- C., Materials Foreign to the Site: N/A.
- D. Access Roads: No additional roads will be required.

7. Methods for Handling Waste Disposal

- A. Cuttings:
 Cuttings will be contained in the reserve pit.
- B. Drilling Fluids: Drilling fluids will be retained in the reserve pit.
- C. Produced Fluids:
 Produced fluids, including produced water will be collected in the reserve pit. Any small amount of hydrocarbon that may be produced during testing will be retained in the reserve pit. Prior to clean up operations, the hydrocarbon material will be skimmed.

7. Methods for Handling Waste Disposal (Cont'd)

- D. Sewage: Sanitary facilities for sewage disposal will consist of at least one pit toilet, during the driller operations. The pit will be backfilled immediately following completion of the drilling operation.
- E. Garbage:
 There probably will not be much putriscible garbage to dispose of. However, it will be disposed of along with the refuse in a constructed burn pit, which will be fenced. The small amount of refuse will be burned and the pit will be covered with a minimum 36 inch cover upon completion.
- F. Clean-Up of Well Site:
 Upon the release of the drilling rig, the surface of the drilling pad will be prepared to accommodate a completion rig, if testing indicates potential productive zones. In either case, the "mouse hole" and "rat hole" will be covered to eliminate a potential hazard to livestock. The reserve pit will be fenced to prevent entry of livestock until the pit is backfilled. Reasonable clean up will be performed prior to final restoration of the site.

8. Ancillary Facilities

None required.

9. Well Site Layout

- A. See Exhibit IV
- B. Location of pits, etc. See Exhibit IV
- C. Rig orientation etc. See Exhibit IV
- D. Lining of pits:
 Pits will not be lined. They will be covered with a fine mesh netting, if necessary, for the protection of wildlife if fluids are found to be toxic.

10. Plans for Restoration of Surface

A. Reserve pit clean up:
The pit will be fenced prior to rig release and shall be maintained until clean up. Prior to backfilling any hydrocarbon material on the pit surface will be removed. The fluids and solids contained in the pit shall be backfilled with soil excavated from the site and with soil adjacent to the reserve pit. The restored surface of the reserve pit will be contoured as needed to minimize erosion. The reserve pit area will be seeded per BLM recommendations during the appropriate season following final restoration of the site.

10. Plans for Restoration of Surface (Cont'd)

- B. Restoration Plans Production Developed:

 The reserve pit will be backfilled and restored as described under Item A. In addition, those disturbed areas not required for production will be graded to blend with the surrounding topography, and seeded, per BLM recommendations. The portion of the drill pad required for production and turning areas will be graded to minimize erosion and provide access to production facilities under inclement conditions. Following depletion and abandonment of the site, restoration procedures will be those under Item C. below.
- C. Restoration Plan No Production Developed:
 The reserve pit will be restored as described above. With no production developed, the entire surface disturbed by construction of the drilling pad will be restored. The site will be contoured to blend with the surrounding topography. The site will be seeded according to BLM recommendations. If the new access road is not required for other development plans, it will be obliterated and restored and seeded per BLM recommendations.
- D. Rehabilitation Time Table:
 Upon completion of operations the intial clean up of the well site will be performed. Final restoration of the site will be performed as soon as possible according to procedural guidelines published by the USGS and BLM. Seeding of the disturbed areas which are no longer required will be performed during the appropriate season, following final restoration.

11. Other Information

- A. Surface Description: The surface description of the proposed wellsite location is located approximately 1 1/2 miles southeast of Manzarnares Canyon. The terrain consists of sandy soil,
 Juniper and pine trees on the north end.
- B. Surface Use Activities:
 The surface is federally owned and managed by the BLM. The predominant surface use is mineral exploration and production.
- C. Proximity of Water, Dwellings and Historical Sites:
 - 1. Water:
 There are no reservoirs or streams in the immediate area.
 - 2. Occupied Dwellings:
 There are no occupied dwellings or buildings in the area.
 - 3. Sites:
 An archeological reconnissance has been performed for this location and clearance has been granted.

12. Operator's Field Representative


Donald S. Barnes
Division Drilling Engineer
Tenneco Oil Company
720 South Colorado Blvd.
Penthouse
Denver, CO 80222
(303) 758-7130 Ext. 212

13. Certification

I hereby certify that I, or persons under my direct supervision, have inspected the proposed drill site and access route; that I am familiar with the conditions as they actually exist; that the statements made in this plan are, to the best of my knowledge, true and correct; and that the proposed work performed by Tenneco Oil Company and its contractors and subcontractos will conform to this plan.

Date: 9-4-79

J. M. Zacey Division Production Manager



TENNECO OIL COMPANY

CALCULATION SHEET

EXHIBIT IV DRILLING WELL SITE LAYOUT HUGHES #5 SUBJECT 965' FNL, 1540' FWL, SEC. 20, T 29N, R 8W DATE: 8-79 SAN JUAN COUNTY, NEW MEXICO 100 -BUNK HOUSE RESERVE PITS 100' PIT 135 DRILLING RIG MUD PRESENT ROAD WELL \oplus FLARE PIT 20 PIPE CAT RACKS 175 C 8 1 BURN C 8' 20 ° PARKING