

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

30-047 24031

APPLICATION FOR PERMIT TO DRILL, DEEPEN, OR PLUG BACK

1a. TYPE OF WORK

DRILL ☒

DEEPEN ☐

PLUG BACK ☐

b. TYPE OF WELL

OIL  
WELL ☐

GAS  
WELL ☒

OTHER

SINGLE  
ZONE ☐

MULTIPLE  
ZONE ☐

2. NAME OF OPERATOR

TENNECO OIL COMPANY

3. ADDRESS OF OPERATOR

720 S. Colorado Boulevard, Denver, Colorado 80222

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.)\*

At surface

860 FSL 1150 FWL

At proposed prod. zone

14. DISTANCE IN MILES AND DIRECTION FROM NEAREST TOWN OR POST OFFICE\*

11.6 East of Bianco, New Mexico

15. DISTANCE FROM PROPOSED\*

LOCATION TO NEAREST  
PROPERTY OR LEASE LINE, FT.  
(Also to nearest drig. unit line, if any)

18. DISTANCE FROM PROPOSED LOCATION\*

TO NEAREST WELL, DRILLING, COMPLETED,  
OR APPLIED FOR, ON THIS LEASE, FT.

16. NO. OF ACRES IN LEASE

1840.00

19. PROPOSED DEPTH

8,200

17. NO. OF ACRES ASSIGNED  
TO THIS WELL

320

20. ROTARY OR CABLE TOOLS

Rotary

21. ELEVATIONS (Show whether DF, RT, GR, etc.)

6907 GR

22. APPROX. DATE WORK WILL START\*


ASAP

23.

PROPOSED CASING AND CEMENTING PROGRAM

SIZE OF HOLE	SIZE OF CASING	WEIGHT PER FOOT	SETTING DEPTH	QUANTITY OF CEMENT
13 3/4"	9 5/8" New	36# K-55	300 ±	Circulate to surface
8 3/8"	7" New	23# K-55	3500 ±	Circulate to surface
6 1/4"	4 1/2" New	10.5# 11.6#	8200 ±	Circulate to liner hanger

Gas Is Dedicated



IN ABOVE SPACE DESCRIBE PROPOSED PROGRAM: If proposal is to deepen or plug back, give data on present productive zone and proposed new productive zone. If proposal is to drill or deepen directionally, give pertinent data on subsurface locations and measured and true vertical depths. Give blowout preventer program, if any.

24.

SIGNED M. L. Freeman

TITLE Staff Production Analyst

DATE 11-20-79

(This space for Federal or State office use)

PERMIT NO. \_\_\_\_\_

APPROVAL DATE \_\_\_\_\_

APPROVED BY \_\_\_\_\_

TITLE \_\_\_\_\_

DATE \_\_\_\_\_

CONDITIONS OF APPROVAL, IF ANY:

ok Frank

NMOCC

DRILLING OPERATIONS AUTHORIZED ARE  
SUBJECT TO COMPLIANCE WITH ATTACHED  
"GENERAL REQUIREMENTS"

\*See Instructions On Reverse Side

All distances must be from the outer boundaries of the Section.


Operator <b>TENNECO OIL COMPANY</b>			Lease <b>VANDEWART</b>		Well No. <b>2</b>
Unit Letter <b>M</b>	Section <b>13</b>	Township <b>29N</b>	Range <b>8W</b>	County <b>San Juan</b>	
Actual Footage Location of Well: <b>860</b> feet from the <b>South</b> line and <b>1150</b> feet from the <b>West</b> line					
Ground Level Elev. <b>6907</b>	Producing Formation <b>Dakota</b>		Pool <b>Basin Dakota</b>	Dedicated Acreage: <b>320</b> Acres	

1. Outline the acreage dedicated to the subject well by colored pencil or hatchure marks on the plat below.
2. If more than one lease is dedicated to the well, outline each and identify the ownership thereof (both as to working interest and royalty).
3. If more than one lease of different ownership is dedicated to the well, have the interests of all owners been consolidated by communitization, unitization, force-pooling, etc?

☐ Yes ☐ No If answer is "yes," type of consolidation \_\_\_\_\_

If answer is "no," list the owners and tract descriptions which have actually been consolidated. (Use reverse side of this form if necessary.) \_\_\_\_\_

No allowable will be assigned to the well until all interests have been consolidated (by communitization, unitization, forced-pooling, or otherwise) or until a non-standard unit, eliminating such interests, has been approved by the Commission.



CERTIFICATION

I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief.

Name  
*M. A. Furman*  
Position  
Staff Production Analyst  
Company  
TENNECO OIL COMPANY  
Date  
11-20-79

I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my knowledge and belief.

Date Surveyed  
July 21, 1979  
Registered Professional Engineer and/or Land Surveyor  
*Fred B. Kerr, Jr.*  
Fred B. Kerr, Jr.  
Certificate No.  
3950

1. The geological name of the surface formation is Tertiary San Jose
- 2&3. Estimated Formation Tops:

Ojo	2550'	Mancos	5953'
Pictured Cliffs	3508'	Gallup	6930'
Cliffhouse	5230'	Greenhorn	
Menefee	5380'	Dakota "A"	8008'
Point Lookout	5818'	T.D.	8200'

4. Drill a 13 3/4" hole to 300<sup>+</sup>. Run 9 5/8", 36#, K-55 ST&C casing to 300<sup>+</sup> and circulate cement to surface using 2% CaCl<sub>2</sub> in cement. Drill out shoe and reduce hole to 8 3/4". Drill 8 3/4" hole to 3500<sup>+</sup>. Run 7", 23#, K-55 ST&C casing to 3500<sup>+</sup> and circulate cement to surface. Drill out of 7" with 6 1/4" bit using gas as circulating fluid. Drill to total depth. If productive, run 4 1/2" casing. Cement in one stage and bring cement to above Mesaverde Zone. If nonproductive, P&A as per U.S.G.S. requirements.
5. Blowout Preventors:  
Hydraulic double ram, 10". One set of rams will be provided each size drill pipe in the hole. One set of blind rams at all times. Fill line will be 2", kill line will be 2", choke relief line will be 2". BOP's, drills, and tests will be recorded in the driller's log. BOP will be tested every 24 hours and recorded in IADC log.
6. Mud Program: (Sufficient quantity of mud and weight material will be available on location.)  

0-300 <sup>+</sup>	Spud mud.
300-355 <sup>+</sup>	Low solids fresh water mud. No WL control.
3500-T.D.	Gas.

7. Auxiliary Equipment:
  - a. Kelly cock will be in use at all times.
  - b. Stabbing valve to fit drill pipe will be present on floor at all times.
  - c. Mud monitoring will be visual. No abnormal pressures are anticipated.
  - d. Floats at bits.
  - e. Drill string safety valve(s) to fit all pipe in drill string will be maintained on the rig floor while drilling operations are in progress.
8. Coring, Logging, and Testing Program:

No cores will be taken. Samples will be taken as directed by wellsite geological engineer. GR/FDC/CNL caliper from T.D. to base of Mesaverde. GR/SP/SN induction from T.D. to surface casing.

9. No abnormal pressures or temperatures are anticipated.
10. The drilling of this well will take approximately 10 days.
11. Your office (telephone ) will be notified of spudding in sufficient time to witness cementing operations. Immediate notice will be given on blowouts, fires, spills, and accidents involving life threatening injuries or loss of life. Prior approval will be obtained before appreciably changing drilling program or commencing plugging operations, plug back work, casing repair work or corrective cementing operations.

VANDEWART #2

1. Existing Roads

- A. Proposed Well Site Location: The proposed wellsite location was surveyed and staked by a registered land surveyor and is located 860' FSL, 1150' FWL, Sec.13 T29N-R8W, San Juan County, New Mexico. (See Exhibit I acreage dedication plan).
- B. Planned Access Route: Planned access route begins in Blanco, New Mexico following Highway 64 east for approximately 8-1/2 miles, turn south onto blacktop road and proceed for 3/4 mile south and 2-1/2 miles east. Turn north into wellsite location. (See Exhibit II).
- C. Access Road Labelled:  
  
Color Code:      Red - Improved Surface  
                    Blue - New Access Road
- D. Not applicable - the proposed well is a development well.
- E. The proposed well is a development well. See Exhibit II for existing roads within a one mile radius.
- F. Existing Road Maintenance or Improvement Plan:  
The existing roads will require minimal maintenance.

2. Planned Access Roads

(All roads are existing roads.)

- A. Width:  
The average width of the road is twenty feet.
- B. Maximum Grades:  
Maximum grades will be 6%.
- C. Turnouts:  
There are no turnouts planned as sight distance is sufficient.
- D. Drainage Design:  
The road is center crowned to allow drainage. The road is flat primarily.
- E. Culverts Use Major Cuts and Fills:  
No culverts or major cuts or fills will be required.
- F. Surfacing Material:  
Native soil has been wetted, bladed and compacted to make the road surface, which is existing.

2. Planned Access Roads (Cont'd)

- G. Gates, Cattleguards, Fence Cuts:  
No gates, cattleguards or fences will be needed.
- H. New Roads Centerlined Flagged:  
Existing Roads.

3. Location of Existing Wells

The proposed well is a development well. Exhibit III shows existing wells within a one mile radius.

- A. Water Wells: None
- B. Abandoned Wells: None
- C. Temporarily Abandoned Wells: None
- D. Disposal Wells: None
- E. Drilling Wells: See Exhibit III
- F. Producing Wells: See Exhibit III
- G. Shut-In Wells: None
- H. Injection Wells: None
- I. Monitoring or Observation Wells: None.

4. Location of Existing and/or Proposed Facilities

- A. Existing facilities within one mile owned or controlled by Lessee/Operator:

- (1) Tank batteries - None
- (2) Production facilities - Exhibit III
- (3) Oil Gathering Lines - None
- (4) Gas Gathering Lines - None
- (5) Injection Lines - None
- (6) Disposal Lines - None

- B. New facilities in the event of production:

- (1) New facilities will be within the dimensions of the drill pad.
- (2) Dimensions are shown on Exhibit IV.

- (3) Construction Materials/Methods:  
Construction materials will be native to the site.  
Facilities will consist of a well pad.

- (4) Protection of Wildlife/Livestock:

Facilities will be fenced as needed to protect wildlife or livestock.

4. Location of Existing and/or Proposed Facilities (Cont'd)

B. New facilities in the event of production: (cont'd)

(5) New facilities will consist of wellhead, tank and production unit.

C. Rehabilitation of Disturbed Areas:

Following the completion of construction, those areas required for continued production will be graded to provide drainage and minimize erosion. Those areas unnecessary for use will be graded to blend with surrounding topography per BLM recommendations.

5. Location and Type of Water Supply

A. Location and type of water supply:

Water will be hauled from a private source.

B. Water Transportation System:

Water trucks will be used.

C. Water wells:

N/A.

6. Source of Construction Materials

A. Materials:

Construction materials will consist of soil native to the site. Any topsoil, if present, will be stripped and stockpiled as needed.

B. Land Ownership;

The planned site and access road is on federal land administered by the Bureau of Land Management.

C. Materials Foreign to the Site:

N/A.

D. Access Roads:

No additional roads will be required.

7. Methods for Handling Waste Disposal

A. Cuttings:

Cuttings will be contained in the reserve pit.

B. Drilling Fluids:

Drilling fluids will be retained in the reserve pit.

C. Produced Fluids:

Produced fluids, including produced water will be collected in the reserve pit. Any small amount of hydrocarbon that may be produced during testing will be retained in the reserve pit. Prior to clean up operations, the hydrocarbon material will be skimmed.

7. Methods for Handling Waste Disposal (Cont'd)

- D. Sewage:  
Sanitary facilities for sewage disposal will consist of at least one pit toilet, during the driller operations. The pit will be backfilled immediately following completion of the drilling operation.
- E. Garbage:  
There probably will not be much putrescible garbage to dispose of. However, it will be disposed of along with the refuse in a constructed burn pit, which will be fenced. The small amount of refuse will be burned and the pit will be covered with a minimum 36 inch cover upon completion.
- F. Clean-Up of Well Site:  
Upon the release of the drilling rig, the surface of the drilling pad will be prepared to accommodate a completion rig, if testing indicates potential productive zones. In either case, the "mouse hole" and "rat hole" will be covered to eliminate a potential hazard to livestock. The reserve pit will be fenced to prevent entry of livestock until the pit is backfilled. Reasonable clean up will be performed prior to final restoration of the site.

8. Ancillary Facilities

None required.

9. Well Site Layout

- A. Exhibit IV
- B. Location of pits, etc. See Exhibit IV,
- C. Rig orientation etc. See Exhibit IV.
- D. Lining of pits:  
Pits will not be lined. They will be covered with a fine mesh netting, if necessary, for the protection of wildlife if fluids are found to be toxic.

10. Plans for Restoration of Surface

- A. Reserve pit clean up:  
The pit will be fenced prior to rig release and shall be maintained until clean up. Prior to backfilling any hydrocarbon material on the pit surface will be removed. The fluids and solids contained in the pit shall be backfilled with soil excavated from the site and with soil adjacent to the reserve pit. The restored surface of the reserve pit will be contoured as needed to minimize erosion. The reserve pit area will be seeded per BLM recommendations during the appropriate season following final restoration of the site.

10. Plans for Restoration of Surface (Cont'd)

- B. Restoration Plans - Production Developed:  
The reserve pit will be backfilled and restored as described under Item A. In addition, those disturbed areas not required for production will be graded to blend with the surrounding topography, and seeded, per BLM recommendations. The portion of the drill pad required for production and turning areas will be graded to minimize erosion and provide access to production facilities under inclement conditions. Following depletion and abandonment of the site, restoration procedures will be those under Item C. below.
- C. Restoration Plan - No Production Developed:  
The reserve pit will be restored as described above. With no production developed, the entire surface disturbed by construction of the drilling pad will be restored. The site will be contoured to blend with the surrounding topography. The site will be seeded according to BLM recommendations. If the new access road is not required for other development plans, it will be obliterated and restored and seeded per BLM recommendations.
- D. Rehabilitation Time Table:  
Upon completion of operations the initial clean up of the well site will be performed. Final restoration of the site will be performed as soon as possible according to procedural guidelines published by the USGS and BLM. Seeding of the disturbed areas which are no longer required will be performed during the appropriate season, following final restoration.

11. Other Information

- A. Surface Description: Surface description of the proposed wellsite location is located approximately 3 miles east of Manzanares. The terrain consists of sand, some rock, sagebrush and juniper trees.
- B. Surface Use Activities:  
The surface is federally owned and managed by the BLM. The predominant surface use is mineral exploration and production.
- C. Proximity of Water, Dwellings and Historical Sites:
  - 1. Water:  
There are no reservoirs or streams in the immediate area.
  - 2. Occupied Dwellings:  
There are no occupied dwellings or buildings in the area.
  - 3. Sites:  
An archeological reconnaissance has been performed for this location and clearance has been granted.



12. Operator's Field Representative

Donald S. Barnes  
Division Drilling Engineer  
Tenneco Oil Company  
720 South Colorado Blvd.  
Penthouse  
Denver, CO 80222  
(303) 758-7130 Ext. 212

13. Certification

I hereby certify that I, or persons under my direct supervision, have inspected the proposed drill site and access route; that I am familiar with the conditions as they actually exist; that the statements made in this plan are, to the best of my knowledge, true and correct; and that the proposed work performed by Tenneco Oil Company and its contractors and subcontractors will conform to this plan.

Date: Nov 21, 1979



M. L. Freeman  
Staff Production Analyst

## TENNECO OIL COMPANY

## CALCULATION SHEET


EXHIBIT IV


SUBJECT DRILLING WELL SITE LAYOUT VANDEWART #2

LOCATION 860' FSL, 1150' FWL, SEC. 13, T 29N, R 8W

DATE: 8-79

SAN JUAN COUNTY, NEW MEXICO





All equipment to be 3,000 psi working pressure except as noted.

- Rd Double ram type preventer with two sets of rams.
- R Single ram type preventer with one set of rams.
- S Drilling spool with side outlet connections for choke and kill lines.
- G Rotating head 150 psi working pressure minimum

#### ARRANGEMENT C

TENNECO OIL COMPANY  
 ROCKY MOUNTAIN DIVISION  
 REQUIRED MINIMUM  
 BLOWOUT PREVENTER AND  
 CHOKE MANIFOLD




EXHIBIT III  
VANDEWART #2  
860' FSL, 1150' FWL  
SEC. 13, T 29N, R 8W  
SAN JUAN COUNTY, NEW MEXICO



**Tenneco Oil**  
A Tenneco Company

Penthouse  
720 South Colorado Blvd.  
Denver, Colorado 80222  
(303) 758-7130



November 20, 1979

Mr. Jim Simms  
US Geological Survey  
P.O. Box 959  
Farmington, New Mexico 87401

Re: Vandewart #2  
860 FSL 1150 FWL  
Sec 13 T29N R8W

Dear Mr. Simms:

The subject well was staked in Violation of Title 30 CFR part 221.20 due to topographic problems in the SW/SW of Sec 13. We therefore, respectfully request permission for clearance of a Non Standard location.

Sincerely,

TENNECO OIL COMPANY

A handwritten signature in black ink, appearing to read "M. L. Freeman", is written over a horizontal line.

M. L. Freeman  
Staff Production Analyst

MLF/mh