

5 - USGS 1 - McHugh 1 - Devon 1 - Conoco 1 - El Paso Expl. 1 - File

Form Approved.
Budget Bureau No. 42-R1424

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other ☐
2. NAME OF OPERATOR
Jerome P. McHugh
3. ADDRESS OF OPERATOR
P O Box 208, Farmington, NM 87401
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1800' FNL - 790' FWL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

SUBSEQUENT REPORT OF:

☒ Spud & Surface casing
☐
☒ 7" casing
☐
☐
☐
☐
☐
☐

5. LEASE
SF 078502A
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME
Hardie
9. WELL NO.
#4E
10. FIELD OR WILDCAT NAME
Basin Dakota
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec 24 T29N R8W
12. COUNTY OR PARISH
San Juan
13. STATE
NM
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)
6430' GR

(NOTE: Report results of multiple completion or zone change on Form 9-330)

MAY 13 1981
OIL CON. COM.
DIST. 3

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

5-1-81 Moved in and rigged up Four Corners Drilling Co. Rig #5. Spudded 12-1/4" hole at 7:15 p.m. 4-30-81. Drilled to 225'. Ran 8 jts. 9-5/8" OD, 36#, 8 Rd., ST&C csg. T.E. 212.84' set at 225' RKB. Cemented w/ 135 sx class "B" w/ 2% CaCl. P.O.B. at 2:30 a.m. 5-1-81. Cement to surface.

5-5-81 Ran 76 jts. 7" OD, 20#, 8 Rd., ST&C csg. T.E. 3233.52' set at 3233' RKB. Cemented w/ 175 sx 65-35 poz with 12% gel + 1/4# flocele/sk followed by 150 sx Class "B" with 1/4# flocele/sk. P.O.B. at 10:10 a.m. 5-4-81. Reciprocated pipe OK while cementing. Good mud returns. Trace of cement to surface.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Jim L. Jacobs TITLE Agent DATE 5-5-81

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE MAY 13 1981
CONDITIONS OF APPROVAL, IF ANY.

MAJCC