

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other ☐
well well

2. NAME OF OPERATOR
Tenneco Oil Company

3. ADDRESS OF OPERATOR
P. O. Box 3249, Englewood, CO 80155

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 635' FSL 715' FEL "P"
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

SUBSEQUENT REPORT OF

☐
☐
☐
☐
☐
☐
☐
☐
☒

RECEIVED

MAY 21 1982

(NOTE: Report results of multiple completion or zone change on Form 9-330.)
U.S. GEOLOGICAL SURVEY
FARMINGTON, N. M.

5. LEASE
SF-078415

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
Roelofs Com

9. WELL NO.
5

10. FIELD OR WILDCAT NAME
Basin Dakota

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 10, T29N R8W

12. COUNTY OR PARISH | 13. STATE
San Juan | NM

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
6267' - pr.

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

4/27/81 - Mix mud. GIH to 3520', fill hole and circ. RHH and circ @ 7514'.
Plug as per GS requirements:

Plug #1 - depth 7514-7127', 70 sx C1-B for 387'
Plug #2 - depth 6689-6389', 55 sx C1-B for 300'
Plug #3 - depth 5347-5159', 35 sx C1-B for 188'

4/28/81 - Finish plugging well.

Plug #4 - depth 4832-4550', 55 sx C1-B for 282'
Plug #5 - depth 3603-3503', 20 sx C1-B for 100'
Plug #6 - depth 1800-1700', 20 sx C1-B for 100'
Plug #7 - depth 50-0', 10 sx C1-B for 50'

Rig released @ 10:30 a.m. 4/8/82. Installed dry hole marker (10' x 4-1/2") 4' above ground.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Denise Wilson TITLE Production Analyst DATE 5/17/82

Denise Wilson

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

APPROVED

AUG 11 1982
For JAMES F. SIMS
DISTRICT ENGINEER

TITLE _____ DATE _____

*See Instructions on Reverse Side

NMOCC