

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other ☐
2. NAME OF OPERATOR  
Jerome P. McHugh
3. ADDRESS OF OPERATOR  
P O Box 208, Farmington, NM 87401
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 1520' FSL - 2120' FWL  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

5. LEASE  
SF 078416
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME  
Hardie
9. WELL NO.  
#1E
10. FIELD OR WILDCAT NAME  
Basin Dakota
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Sec 26 T29N R8W
12. COUNTY OR PARISH  
San Juan
13. STATE  
NM
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)


REQUEST FOR APPROVAL TO:

- TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐  
(other) ☐

SUBSEQUENT REPORT OF:


- ☒ Spud & surface csg.  
☒ 7" Intermediate csg.

(NOTE: Report results of multiple completion or zone change on Form 9-330.)



17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

See reverse for reports of spud and surface csg 5-11-81 and 7" intermediate csg. 5-14-81.



Subsurface Safety Valve: Manv. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Thomas A. Drigan TITLE Agent DATE 5-13-81

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_

CONDITIONS OF APPROVAL IF ANY:

ACCEPTED FOR RECORD

MAY 18 1981

ANMOCC

FARMINGTON DISTRICT

dugan production corp.

JEROME P. McHUGH

Hardie #1E

1520' FSL - 2120' FWL

Sec 26 T29N R8W

San Juan County, NM

MORNING REPORT

5-11-81 688 - Drilling w/ wtr. 3/4° at 216'

MI & RU Rig #5. Spudded 12-1/4" hole at 10:45 a.m. 5-10-81. Drilled to 220'. Ran 8 jts. 9-5/8" OD, 36#, K-55 csg. T.E. 202.98' set at 216' RKB. Cemented w/ 135 sx class "B" w/ 2% CaCl. P.O.B. at 4:00 p.m. 5-10-81. Good cement to surface. Approx. 3 bbls.)

JEROME P. McHUGH

Hardie #1E

Page 2

5-14-81 Depth 3627' - Drilling w/ air 150 psi  
Ran 79 jts. 7" OD, 20#, K-55, 8 Rd, ST&C csg. T.E. 3196.30' set at 3167' RKB. Cemented by Dowell w/ 175 sx 65-35 plus 12% gel & 1/4# cello flake per sk followed by 150 sx class "B" neat w/ 1/4# cello flake per sk. (Total slurry 635.5 cu.ft.) Cement circulated. Bumped plug w/ 1800 spi. Float failed to hold. Closed in for 2 hrs. Set 7" csg. slips. Cut off csg. Nippled up to drill w/ air.

175  
150  
325