## UNITED STATES DEPARTMENT OF THE INTERIOR **GEOLOGICAL SURVEY**

1	Budget Bureau No. 42–R1424						
5.	LEASE						
S	F-078046						
6.	IF INDIAN, ALLOTTEE OR TRIBE NAME						
7.	UNIT AGREEMENT NAME						
8.	FARM OR LEASE NAME						
Н	ughes						
9.	WELL NO.						
3	E						
10.	FIELD OR WILDCAT NAME						

SU	NDRY	NOT	<b>ICES</b>	AND	REPO	RTS	ON	WELL:	S
(Do not u: reservoir,	se this f Use For	orm for n 9–331-	proposa –C for s	is to drill uch propo	or to deepe sals.)	norp	lug bac	k to a diff	erent
1. oil		gas	হিন						

well X other well 2. NAME OF OPERATOR Tenneco Oil Company 3. ADDRESS OF OPERATOR P. O. Box 3249, Englewood, CO 80155 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 AT SURFACE: 985' FNL 1000' FEL "A"

Basin Dakota 11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 20, T29N R8W

AT TOP PROD. INTERVAL:

12. COUNTY OR PARISH 13. STATE San Juan New Mexico

AT TOTAL DEPTH:

14. API NO.

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

15. ELEVATIONS (SHOW DF, KDB, AND WD)

6555 gr. SUBSEQUENT REPORT OF REQUEST FOR APPROVAL TO: RECEIVED TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL U. S. GEOLOGICAL SURVEY change on Form 9-330.) PULL OR ALTER CASING MULTIPLE COMPLETE FARMINGTON, N. M. CHANGE ZONES ABANDON\* (other)

(NOTE: Report results of multiple completion of OIL CON. COM. DIST. 3

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

6/13/81 - Drill to TD @ 7745'. Blow hole. TOOH. Log well. Log open hole. TIH. TOOH -

6/14/81 - Laid down drill pipe and collars. RU and run 20 jts (879.18') of 4-1/2" 11.6# STC K-55 and 78 jts (4166.14') 4-1/2" 10.5# STC K-55 csg and liner hanger. Set @ 7743' w/top of liner @ 3567'. Cmt w/380 sx 65/35 POZ w/6% gel, .5% CFR-2. Tail in w/150 sx Class G w/.5% Halad-9. Plug down. Circ cmt to top of liner. NDBOP. Release rig 6/15/81.

Subsurface Safety Valve: Manu. and Type Set @ .\_\_\_

18. I hereby certify that the foregoing is true and correct

MATITLE ASST. DIV. Adm. Mgr. DATE \_ (This space for Federal or State office use)

DATE

ASSEPTED FOR RECORD

APPROVED BY CONDITIONS OF APPROVAL, IF ANY:

SIGNED

\*See Instructions on Reverse Side