

10-160-5  
December 1983)  
10-160-5 (331)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPLICATE\*  
(Other instructions on re-  
verse side)

Form approved.  
Budget Bureau No. 1001  
Expires August 31, 1988

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT" for such proposals.)

5. LEASE DESIGNATION AND RECORD

SF-078414

6. IF INDIAN, ALLOTTEE OR TRIBE

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Day B

9. WELL NO.

#13

10. FIELD AND POOL, OR WILDCAT

Basin Fruitland Coal

11. SEC. T. R. M., OR BLK. AND  
SURVEY OR AREA

NWSW Sec8-T29N-R8W

12. COUNTY OR PARISH 13. STATE

San Juan

NM

14. NAME OF OPERATOR  
McKenzie Methane Corporation

15. ADDRESS OF OPERATOR

1911 Main #255, Durango, Colorado 81301

16. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.  
See also space 17 below.)

At surface  
2110' FSL, 930' FWL

17. ELEVATIONS (Show whether DF, RT, GR, etc.)

API 30-045-27454

6355' GR

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

Drilling Report

(NOTE: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)

18. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting and proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Operator Change from Amoco  
Prod. Co.

SEE ATTACHED

RECEIVED  
NOV 5 - 1990  
OIL CON. DIV.  
DIST. 3

19. I hereby certify that the foregoing is true and correct

SIGNED

HQ Sagle / CS

TITLE Operations Manager

DATE 10-19-90

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

ACCEPTED FOR RECORD  
DATE

NOV 01 1990

FARMINGTON RESOURCE AREA

BY

\*See Instructions on Reverse Side

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

**MCKENZIE METHANE CORPORATION**  
**DAILY DRILLING REPORT**  
**Durango Office**

10-13-90      Day B #13  
NWSW Sec8-T29N-R8W, San Juan Co., NM  
AART: DRLG                  DEPTH: 143'  
DAILY: MIRU 4 States #1. Drill mouse & rat hole.  
**SPUD 12-1/4" hole @ 10:00 AM 10-12-90. Drill to 143'.**  
MUD: Spud                  Surveys: N/A

10-14-90      Day B #13  
NWSW Sec8-T29N-R8W, San Juan Co., NM  
AART: DRLG                  DEPTH: 785'  
DAILY: Drill to 260'. Circ & TOOH. Run 6 jts,  
8-5/8", 24#, K55, STC (242') set @ 253'. Cement  
w/ 185 sx (218 cu ft) class B, 2% CaCl. PD @ 11:00  
A.M. 10/13/90. Circ 13 bbl cmt. WOC. NUBOP.  
PT BOP & csg. Drill out cement & open hole to 785'.  
MUD: water                  Surveys: 250' - 3/4, 785' - 1.

10-15-90      Day B #13  
NWSW Sec8-T29N-R8W, San Juan Co., NM  
AART: DRLG                  DEPTH: 2060'  
DAILY: Drill to 2060'.  
MUD: 9.0                  Vis: 32      Surveys: 1286' - 1-1/2,  
1781' - 1-1/4.

10-16-90      Day B #13  
NWSW Sec8-T29N-R8W, San Juan Co., NM  
AART: Circ for logs                  DEPTH: 2895'  
DAILY: TD well @ 5:30 A.M. 10-16-90. Circ &  
condition hole for logs.  
MW: 9.0                  Vis: 45      Surveys: 2275' - 1,  
2768' - 1.

**McKENZIE METHANE CORPORATION**  
**DAILY DRILLING REPORT**  
**Durango Office**

10-17-90

Day B #13  
NWSW Sec8-T29N-R8W, San Juan Co., NM  
AART: DRIG DEPTH: 3110'  
DAILY: TOOH for logs. Log openhole. Well not  
deep enough. TTH & drill to 3110'. Revised  
TD @ 3120'. MW: 9.0 VIS: 45  
Surveys: N/A  
-----

10-18-90

Day B #13  
NWSW Sec8-T29N-R8W, San Juan Co., NM  
AART: Moving DEPTH: 3120'  
DAILY: Drill to 3120'. Circ & TOOH for logs. Log  
openhole w/ Atlas. TTH & circ for csg. TOOH. LDDP.  
Run 105 jts (3109'), 5-1/2", 17#, J55, LTC csg set  
@ 3119'. Float collar @ 3071'. Cement w/ 470 sx  
(865 cu ft) 65/35 POZ, 6% gel, 10% salt, 1/4#/sx  
cellophane flakes followed by 100 sx (121 cu ft)  
Class G, 2% CaCl, 1/4#/sx cellophane flakes. PD  
@ 6:00 A.M. 10-18-90. Circ 10 bbl cmt. NDBOP.  
Set slips & cut off csg. Release rig. MORT.  
MUD: N/A Surveys: 3120' - 1.