STATE OF NEW MEXICO ENERGY and MINERALS DEPARTMENT

## **OIL CONSERVATION DIVISION**

Page 1 Revised 10/01/78

This form is not to be used for reporting packer leakage tests in Southeast New Mexico

## NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

Well 1B SUNRAY No. Lease BURLINGTON RESOURCES OIL & GAS CO. Operator Location SAN JUAN W800 County 029N Roe. Twp of Well: Unit F Sect 05 METHOD OF PROD PROD. MEDIUM TYPE OF PROD. NAME OF RESERVOIR OR POOL (Tbg. or Csg.) (Oil or Gas) (Flow or Art. Lift) Upper Flow Tubing Gas **MESAVERDE** Completion Lower Flow Tubing Gas DAKOTA Completion PRE-FLOW SHUT-IN PRESSURE DATA Stabilized? (Yes or No) SI press. psig Length of time shut-in Hour, date shut-in Upper 175 Completion 72 Hours 06/18/2001 Lower 391 Completion 06/18/2001 24 Hours FLOW TEST NO. 1 LOWER Zone producing (Upper or Lower) 06/19/2001 Commenced at (hour.date)\* **PRESSURE** PROD. ZONE TIME LAPSED TIME TEMP REMARKS Lower Completion SINCE\* Upper Completion (hour.date) 435 186 06/20/2001 48 Hours 188 154 72 Hours 06/21/2001 Production rate during test GOR Grav. Bbls. in Hours. BOPD based on Oil MCFPD: Tested thru (Orifice or Meter): Gas MID-TEST SHUT-IN PRESSURE DATA SI press. psig Stabilized? (Yes or No) Length of time shut-in Upper Hour, date shut-in Completion SI press. psig Stabilized? (Yes or No) Length of time shut-in Hour, date shut-in Lower Completion 82033902 380 (Continue on reverse side)

## FLOW TEST NO 2

Commenced at (hour, date)**  Zone producing (Upper or Low(r):						
TIME (hour, date)	LAPSED TIME SINCE **	PRESSURE		PROD. ZONE		
		Upper Completion	Lower Completion		REMARKS	
Production rate dur	ing test					
Oil:	BO	PD based on	Bbls. in _	Hours	Grav GOR	
Gas:		MCFPI	D: Tested thru (Ori	ifice or Meter):		
I hereby certify that	the information here	ein contained is true	and complete to the	he best of my knowledge.		
Approved	JUL 1	2001				
			·	Operator Burlington	Resources	
	Conservation Divis			By Mors L	Circ	
By				Title Operations Associate		
Title DEFUTY OIL & GAS INSPECTOR, DIST. #8				Date Monday, July 09 2001		

## NORTHWEST NEWMEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- 1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tabing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- 2.—At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3 The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. i, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note, if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to lack of a pipeline connection the flow period shall be three hours.
- 5- Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above
- 6 Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except

- that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced
- 7. Pressures for gas-zone tests nust be measured on each zone with a deadweight pressure gauge at time intervals a: follows: 3 hours tests immediately prior to the beginning of each flow period, at fifteen-mir are intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests mediately prior to the beginning of each flow period at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired or may be requested on wells which lave previously shown questionable test data. 24-hour oil zone test, all no suggest throughout the entire test.

24-hour oil zone tests all pressures, throughout the entire test, shall be continuously measured and recorded with recoil ting pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a viell is a gas-oil of an oil-gas dual completion, the recording gauge shall be required in the oil zone only, with deadweight pressures as required above being taken on the gas zone.

8 The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Nor twest New Mexico Packer Leakage Test Form Revised 10-01-78 with all deadweight pressures incicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).