Form ე-5 901 (June

Approved by

Conditions of approval, if any:

UNITED STATES DEPARTMENT OF THE INTERIOR **BUREAU OF LAND MANAGEMENT**

FORM APPROVED

Budget Bureau No. 1004-0135 Expires: March 31, 1993

		-1	
SUNDRY NO Do not use this form for prop	5. Lease Designation and Serial No. SF-078132 6. If Indian, Allogree or Tribe Name		
Use "APPLICA	ATION FOR PERMIT - " for such proposals	7. If Unit or CA, Agreement	Designation
1. Type of Well Oil Well Well Other	8. Weil Name and No.		
2. Name of Operator	Attention:	A. L. Elliott C	2
Amoco Production Company Lois Raeburn		9. API Well No.	
3. Address and Telephone No. P.O. Box 800, Denver, Colorado 80201 (303) 830-5294		30045-08343 10. Field and Pool, or Exploratory Area	
4. Location of Well (Footage, Sec., T., R., M., or Survey Description)		Blanco Pictured Cliffs	
4. Location of Well (Footage, Sec., 1., K., M., or	11. County or Parish, State		
1620FNL 1160FWL Sec. 15 T 29N R 09W		Con lunn	New Mexico
		San Juan	
12. CHECK APPROPRI	ATE BOX(s) TO INDICATE NATURE OF NOTICE, R	REPORT, OR OTHER	RDATA
TYPE OF SUBMISSION TYPE OF ACTION			
Notice of Intent Subsequent Report Final Abandonment Notice		Change of Plans New Construction Non-Routine Fracturing Water Shut-Off Conversion to Injection Dispose Water ort results of multiple completior ion Report and Log form.	n on Well Completion or
13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* Amoco Production Company request permission to Plug and Abandon the above mentioned well.			
See Attached Procedures. If you have any questions ple	ase contact Lois Raeburn @ (303) 830-5294	070 FARWINGTON,	50 July 15 Jul
	DECEIN N Jung 0 1991 OIL GOM, D		Ç
14. I hereby certify that the foregoing is true and	-500 60		06-13-1994
This space for Federal or State office use)			

Title



P&A A L Elliott C 2 - PC Run 34 June 8, 1994

Procedure:

- 1. Move in rig. Rig Up. Nipple up blowout preventer.
- 2. Kill well. Pull tubing.
- 3. Run work string and spot cement across PC zone to at least 2370'(150' above the top of the PC perfs). Pull tubing up out of cement. Apply 500 psi pressure to the cement column to obtain a squeeze. Allow the cement to set for 24 hours.
- 4. Pressure test cement to 1000 psi. Run in with tubing and tag cement top to be sure cement is 150' above the top perf. Set new cement if necessary.
- 5. Fill hole with plugging fluid.
- Test Bradenhead for pressure. Contact Stan Kolodzie if Bradenhead flows gas or water.
 Last available test showed no leakage. If bradenhead leaks, further squeezing will be required.
- 7. Set surface plug 100 feet of cement. Allow cement to set for 24 hours. Pressure test plug to 1000 psi.
- 8. Set P&A marker.
- 9. Remediate or rehabilitate surface location in accordance with federal regulations.

AUTHORIZATIONS

ENGINEER

PRODUCTION FOREMAN

WORKOVER FOREMAN