

Form 9-331
(May 1963)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

SF-078049-A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Bolin-Hardie

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Basin - Dakota

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

34-29N-8W NMPM

12. COUNTY OR PARISH 13. STATE

San Juan

N.M.

1. OIL ☐ GAS ☒ OTHER
WELL WELL

2. NAME OF OPERATOR

Jerome P. McHugh

3. ADDRESS OF OPERATOR

930 Petroleum Club Bldg., Denver, Colorado

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

880' fnl 1170'fwl

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, CR, etc.)

6402-Gr. 6415' RKB

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

8/16/67 Spud 13 3/4" hole 3:00 P.M., 8/15/67. Drill to 212'. Ran 6 jts. 9 5/8" O.D. 32.30# H-40, 8R csg. T.E. 194.98 set at 209' RKB. Cemented w/140 sx. class "C" 2% cacl., good cement returns. POB 11:15 P.M., 8/15/67. W.O.C. 3/4" - 212.

8/21/67 Ran 101 jts. 7" O.D., 28 jts. 20# J-55 & 73 jts. 17# H-40, 8R, ST&C Youngstown casing. T.E. 3212.13 set at 3199 RKB. Cemented w/125 sx. class "C" 40% Diacel "D" and 75 sx. class "C" w/12 1/2# gilsonite per sx. P.O.B. 12:45 P.M., 8/20/67. Lost circulation with 70 bbls of displacement in. Nippled up. Jetting hole down w/gas.

8/27/67 T.D. 7529' Ran 233 jts. 4 1/2" O.D., 26 jts. 11.6#, 207 jts. 10.5# J-55, 8R, ST&C Youngstown csg. T.E. 7541.10 set at 7529 RKB. Cemented w/130 sx. class "C" 40% Diacel "D" 12 1/2# gilsonite per sx., plus 100 sx. class "C" 7 1/2# salt per sx. P.O.B. 2:15 P.M., 8/26/67. Max. cementing press. 1200 psi., followed plug w/250 gal. Acidic acid.

18. I hereby certify that the foregoing is true and correct

SIGNED

James H. McHugh

TITLE

Engineer

DATE

9-15-67

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

*See Instructions on Reverse Side