
DEC 3 0 1997

Meter Number:87554
Location Name:HEATH GAS COM M #1
Location:TN-29 RG-09
SC-09 UL-G
2 - Federal

2 - Federal NMOCD Zone:OUTSIDE Hazard Ranking Score:00



RATIONALE FOR RISK-BASED CLOSURE OF PRODUCTION PITS LOCATED OUTSIDE OF THE VULNERABLE ZONE IN THE SAN JUAN BASIN

This production pit location was ranked according to the criteria in the New Mexico Oil Conservation Division's Unlined Surface Impoundment Closure Guidelines and received a ranking score of zero. The estimated depth to groundwater is greater than 100-feet beneath ground surface (bgs), the pit is not in a well head protection area, and there are no surface water bodies within 1,000 horizontal feet of the pit location.

The primary source, discharge to the pit has been removed. There has been no discharge to the pits for at least 4 years and the pits have been closed for at least one year.

Each pit was backfilled with clean soil and graded in a manner to divert precipitation away from the excavated area. Minimal infiltration of rainfall is expected. Any rainfall that does infiltrate the ground surface must migrate through clean backfill before reaching the residual hydrocarbons.

There is no source material at the ground surface, so direct contact of hydrocarbons with livestock and the populous is not likely.


In general, outside of the vulnerable area and alluvial valleys, bedrock material is generally encountered within 20 feet of the ground surface. Bedrock material in the San Juan Basin consists of interbedded sandstones, shales and clays. According to Freeze and Cherry, 1979, the hydraulic conductivity of the bedrock material are as follows:

Sandstone 10^{-9} to 10^{-13} cm/sec Shale 10^{-12} to 10^{-16} cm/sec Clay 10^{-12} to 10^{-15} cm/sec

Based on this information, the residual hydrocarbons should not migrate to groundwater.

Natural process (bioremediation) are degrading the residual hydrocarbon to carbon dioxide and water and will continue until the source is gone, therefore minimizing any impact to the environment.

Based on the above information, it is highly unlikely that any source material will impact groundwater or ever find an exposure pathway to affect human health and therefore El Paso Field Services Company (EPFS) requests closure of this pit location.



| GENERAL | Meter: 87554 Location: HEATH GAS COM M # 1 Operator #: 0203 Operator Name: AMOCO P/L District: BLOOMFIELD Coordinates: Letter: G Section 9 Township: 29 Range: 9 Or Latitude Longitude Pit Type: Dehydrator Location Drip: X Line Drip: Other: Site Assessment Date: 5.7.94 Area: 10 Run: 53 | | | | | | |
|-----------------|---|--|--|--|--|--|--|
| SITE ASSESSMENT | NMOCD Zone: (From NMOCD Maps) Inside Outside Depth to Groundwater Less Than 50 Feet (20 points) Greater Than 100 Ft (0 points) Wellhead Protection Area: Is it less than 1000 ft from wells, springs, or other sources of fresh water extraction?, or; Is it less than 200 ft from a private domestic water source? Horizontal Distance to Surface Water Body Land Type: BLM (1) State (2) Indian Depth to Groundwater Less Than 50 Feet (20 points) (1) 50 Ft to 99 Ft (10 points) (2) Greater Than 100 Ft (0 points) Wellhead Protection Area: Is it less than 200 ft from a private domestic water source? (1) YES (20 points) Horizontal Distance to Surface Water Body | | | | | | |
| KS | Remarks : DNLY PIT ON LOCATION PIT IS DRY, LOCATION IS UP ON A | | | | | | |
| REMARKS | MESA, REDLINE SHOWS LOCATION IS INSIDE THE VIZ. BUT TOPO SHOWS THAT | | | | | | |
| RE | IT IS OUTSIDE THE WZ. PUSH IN | | | | | | |
| | TWSIT IN | | | | | | |

| | ORIGINAL PIT LOCATION | | | | | |
|-----------------------|---|---|--|--|--|--|
| ORIGINAL PIT LOCATION | Original Pit : a) Degrees from N b) Length : <u>13</u> | orth <u>132°</u> Footage from Wellhead <u>41'</u> Width : <u>12'</u> Depth : <u>2'</u> | | | | |
| | | WELL HEAD 13' | | | | |
| REMARKS | Remarks: TOOK PICTURES AT 2:30 P.M. END DUMP | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | Completed By: | | | | | |
| 1 | | | | | | |
| | February Signature | <u>5.7.94</u> Date | | | | |

FIELD IT REMEDIATION/CLOSUR FORM

| GENERAL | Meter: 87554 Location: Heath Gas com m#1 Coordinates: Letter: 6 Section 9 Township: 29 Range: 9 | | | | | |
|--------------|---|--|--|--|--|--|
| GE | Or Latitude Longitude Date Started : <u>6-7-94</u> Area: <u>10</u> Run: <u>53</u> | | | | | |
| OBSERVATIONS | Sample Number(s): MK 19 Sample Depth: Feet | | | | | |
| | Final PID Reading <u>237</u> PID Reading Depth <u>4'</u> Feet Yes No | | | | | |
| FIELD C | Groundwater Encountered (1) 🗓 (2) Approximate DepthFeet | | | | | |
| URE | Remediation Method: Excavation | | | | | |
| | Envirotech (1) (3) Tierra Other Facility (2) Name: Pit Closure Date: Pit Closed By: | | | | | |
| REMARKS | Remarks: Sed was Grayish black Had strong HyDrocarbon smell Hit Sandstoke Epuc lines were marked | | | | | |
| | Signature of Specialist: Morgan Xillian | | | | | |

(SP3191) 04/07/94



FIELD SERVICES LABORATORY ANALYTICAL REPORT PIT CLOSURE PROJECT - Soil

SAMPLE IDENTIFICATION

| | OAIIII EE | IDENTITION | | | | | | | | | |
|---|-----------|-----------------|------------------|------------|--------|--------|--|--|--|--|--|
| | Field ID | | | Lab ID | | | | | | | |
| SAMPLE NUMBER: | MK 1 | 945343 | | | ! ! | | | | | | |
| MTR CODE SITE NAME: | 87554 | | N/A | | | | | | | | |
| SAMPLE DATE TIME (Hrs): | 6-7- 91 | | 1500 | | | i I | | | | | |
| SAMPLED BY: | | | | | | | | | | | |
| DATE OF TPH EXT. ANAL.: | 6/10/94 | | 6/10/94 | | | | | | | | |
| DATE OF BTEX EXT. ANAL.: | NIK | | NIK | | | | | | | | |
| TYPE DESCRIPTION: | ٧G | | Grey time Smalla | | | Å | | | | | |
| REMARKS:RESULTS | | | | | | | | | | | |
| | | | | | | | | | | | |
| PARAMETER | RESULT | UNITS | | QUALIFIERS | | | | | | | |
| | | | DF | Q | M(g) | V(ml) | | | | | |
| BENZENE | | MG/KG | | | | | | | | | |
| TOLUENE | | MG/KG | | | | | | | | | |
| ETHYL BENZENE | | MG/KG | | | | | | | | | |
| TOTAL XYLENES | | MG/KG | | - | | | | | | | |
| TOTAL BTEX | | MG/KG | | | | | | | | | |
| TPH (418.1) | 1970 | MG/KG | _ | | 2.03 | 28 | | | | | |
| HEADSPACE PID | 237 | PPM | | · | | | | | | | |
| PERCENT SOLIDS | 92.0 | % | | | | | | | | | |
| - TPH is by EPA Method 418.1 and BTEX is by EPA Method 8020 - | | | | | | | | | | | |
| ne Surrogate Recovery was at | | % for this samp | le All QA/QC | was accep | table. | | | | | | |

6/16/60

)F = Dilution Factor Used

Dothe Sund:

[4/06/10 12:11

Bample Adentification

_ ijiliai maee of sample. g

. Which we of sample with extraction, also so ϵ

Fetnolwer bronocarbons, pos TTO 274

_el absorbance of hydrocarbons .2730 cm-1)

