

Form 9-33
(May 1963)UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPPLICATE*
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

SF 078201A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Lively

9. WELL NO.

5

10. FIELD AND POOL, OR WILDCAT

Basin Dakota

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 1, T29N, R9W

12. COUNTY OR PARISH

San Juan

13. STATE

N.M.

1. OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

Lively Exploration Company

3. ADDRESS OF OPERATOR

Box 234, Farmington, New Mexico 87401

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*

See also space 17 below.)

At surface

990' FSL - 990' FEL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

6430' GR

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

2-1-73

T.D. 7564'. Ran 238 jts 4½" O.D. 10.5# and 11.6# K-55 8R ST&C casing. T.E. 7550.99' set at 7550' RKB. Cemented with 100 sacks Class "C" 40% diacel "D", 12½# gilsonite per sack plus 100 sacks Class "C" 7½# salt per sack. Followed plug with 250 gallons acetic acid. Maximum cementing pressure 1600 psi. Hit pressure with 96 barrels displacement in. P.O.B. 1:10 a.m. 2-1-73. Rig released 4:00 a.m. 5½ hrs logging, 4 hrs lay down drill pipe and collars, 2-¾ hrs go in hole, 1½ hrs rig up to run casing, 4-¾ hrs run 4½" casing, 1½ hrs blow hole, 1 hr cement, 3 hrs pick up B.O.P., set slips and lay down same and nipple up wellhead. Waiting on completion.



FEB 26 1973

U.S. GEOLOGICAL SURVEY

18. I hereby certify that the foregoing is true and correct

SIGNED Original signed by T. A. Dugan

TITLE Engineer

DATE 2-22-73

Thomas A. Dugan

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

