

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPPLICATE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 42-R1424.
5. LEASE DESIGNATION AND SERIAL NO.

NM 03999

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Grambling

9. WELL NO.

3A

10. FIELD AND POOL, OR WILDCAT

Blanco Mesa Verde

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 22, T-29-N, R-9-W
N.M.P.M.

12. COUNTY OR PARISH 13. STATE

San Juan

New Mexico

1. OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

El Paso Natural Gas Company

3. ADDRESS OF OPERATOR

Box 990, Farmington, New Mexico 87401

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*

See also space 17 below.)

At surface

1600' N, 800' W

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

5729' GL

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

09-28-76 T.D. 2418'. Ran 60 joints 7", 20#, KS intermediate casing, 2406' set at 2418'. Cemented with 298 cu. ft. cement. W.O.C. 12 hours, held 1200#/30 minutes.

10-01-76 T.D. 4848'. Ran 82 joints 4 1/2", 10.5#, KS casing liner, 2598' set 2250-4848'. Float collar set at 4831'. Cemented with 450 cu. ft. cement. W.O.C. 18 hours.

10-26-76 P.B.T.D. 4831'. Tested casing to 3500#, O.K. Perfed 3775', 3861', 3880', 3885', 3890', 3908', 3939', 3945', 3948', 3953', 3956', 4125', 4143', 4154', 4198', 4242', 4251', 4260', 4276', 4285' with 1 shot per zone. Fraced with 68,000#--20/40 sand and 70,560 gallons water. No ball sets dropped. Flushed with 4,662 gallons water.

NOV 8 1976

18. I hereby certify that the foregoing is true and correct

SIGNED

J. P. Suarez

TITLE

Drilling Clerk

DATE

November 5, 1976

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE