

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

SE 080000-A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Simmons E

9. WELL NO.

2A

10. FIELD AND POOL, OR WILDCAT

Blanco Mesaverde

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 23-T29N-R9W

N.M.P.M.

12. COUNTY OR PARISH

San Juan

13. STATE

N.M.

1. OIL ☐ GAS ☒ OTHER ☐
WELL WELL

2. NAME OF OPERATOR

Mrs. D. J. Simmons

3. ADDRESS OF OPERATOR

3815 McCart Street
Fort Worth, Texas 76110

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)

At surface 1700' FNL - 790' FWL of Sec. 23 - T29N - R9W

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

5794 GR 5805 KB

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

☐
☐
☐
☐
☐

PULL OR ALTER CASING

☐
☐
☐
☐
☐

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF: Setting

WATER SHUT-OFF

☐
☐
☐
☐
☐

REPAIRING WELL

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT*

(Other) Surface & Intermediate

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

The above captioned well was spudded at 6:00 A.M. on January 14, 1978 and a 13 3/4" surface hole was mud drilled to a depth of approx. 225 feet. At 2:00 P.M. on January 14, 1978 221 feet of 8 9 5/8" 32.3# surface casing was set and cemented with 200 sacks of Class "B" cement with 3% CaCl. Cement circulated to the surface.

On 1-15-78: Prior to drilling out from under surface, a Shaffer 10" - 900 Series, hydraulic closing, double ram (pipe rams & blind rams), 6000 psi test blowout preventer was installed on the 9 5/8" surface casing and the casing was pressure tested to 600 psi and held steady for 30 minutes. An 8 3/4" hole was then mud drilled to a depth of 2692' which was reached at approx. 6:00 P.M. 1-17-78. At approx. 5:00 A.M. 80 joints (2682') of 20# 7" (Intermediate String) casing was set to a KB depth of 2692' and cemented with 200 sacks of (65-35) lite cement followed by 100sacks of Class "B" cement. Well shutin in preparation for gas drilling a 6 1/2" hole on to an approx. T.D. of 4875 ft. at which depth a 4 1/2" liner will be set from T.D. and extending up approx. 200' above the base of the 7" and at this point the 4 1/2" liner will be cemented.

18. I hereby certify that the foregoing is true and correct

SIGNED

Ashton B. Geren, Jr.

TITLE Manager & Supt. for:

Mrs. D. J. Simmons, Opr.

DATE Jan. 18, 1978

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

JAN 18 1978

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.