DEPUTY OIL & GAS INSPECTOR

Meter Number: 70992 70992-2

Location Name:SAN JUAN 30-6 #99 (Pit #2)

Location:TN-30 RG-07

SC-34 UL-M 4 - Fee

NMOCD Zone: OUTSIDE

Hazard Ranking Score:00

DEGEIVED N APR 1 4 1997

RATIONALE FOR RISK-BASED CLOSURE OF PRODUCTION PITS LOCATED OUTSIDE OF THE VULNERABLE ZONE IN THE SAN JUAN BASIN

This production pit location was ranked according to the criteria in the New Mexico Oil Conservation Division's Unlined Surface Impoundment Closure Guidelines and received a ranking score of zero. The estimated depth to groundwater is greater than 100-feet beneath ground surface (bgs), the pit is not in a well head protection area, and there are no surface water bodies within 1,000 horizontal feet of the pit location.

The primary source, discharge to the pit has been removed. There has been no discharge to the pits for at least 4 years and the pits have been closed for at least one year.

Each pit was backfilled with clean soil and graded in a manner to divert precipitation away from the excavated area. Minimal infiltration of rainfall is expected. Any rainfall that does infiltrate the ground surface must migrate through clean backfill before reaching the residual hydrocarbons.

There is no source material at the ground surface, so direct contact of hydrocarbons with livestock and the populous is not likely.

In general, outside of the vulnerable area and alluvial valleys, bedrock material is generally encountered within 20 feet of the ground surface. Bedrock material in the San Juan Basin consists of interbedded sandstones, shales and clays. According to Freeze and Cherry, 1979, the hydraulic conductivity of the bedrock material are as follows:

Sandstone 10^{-9} to 10^{-13} cm/sec Shale 10^{-12} to 10^{-16} cm/sec Clay 10^{-12} to 10^{-15} cm/sec

Based on this information, the residual hydrocarbons should not migrate to groundwater.

Natural process (bioremediation) are degrading the residual hydrocarbon to carbon dioxide and water and will continue until the source is gone, therefore minimizing any impact to the environment.

Based on the above information, it is highly unlikely that any source material will impact groundwater or ever find an exposure pathway to affect human health and therefore El Paso Field Services Company (EPFS) requests closure of this pit location.




FIELD PIT SITE ASSESSMENT FORM

| GENERAL | Meter: 70992 Location: SAN JUAN 30-6 #99 Operator #: Operator Name: MERIDIAN P/L District: Bloom Pisca Coordinates: Letter: M Section 34 Township: 30 Range: 7 Or Latitude Longitude Pit Type: Dehydrator Location Drip: X Line Drip: Other: Site Assessment Date: 2.22.95 Area: 10 Run: 72 | | | |
|-----------------|--|--|--|--|
| SITE ASSESSMENT | NMOCD Zone: (From NMOCD Maps) Inside Outside Land Type: BLM ☐ (1) State ☐ (2) Fee ☒ (3) Indian ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ | | | |
| | Depth to Groundwater Less Than 50 Feet (20 points) 50 Ft to 99 Ft (10 points) Greater Than 100 Ft (0 points) (1) (2) (3) | | | |
| | Wellhead Protection Area: Is it less than 1000 ft from wells, springs, or other sources of fresh water extraction?, or; Is it less than 200 ft from a private domestic water source? ☐ (1) YES (20 points) ☒ (2) NO (0 points) | | | |
| | Horizontal Distance to Surface Water Body Less Than 200 Ft (20 points) (1) 200 Ft to 1000 Ft (10 points) (2) Greater Than 1000 Ft (0 points) (3) Name of Surface Water Body ———— | | | |
| | (Surface Water Body : Perennial Rivers,Major Wash,Streams,Creeks, Irrigation Canals,Ditches,Lakes,Ponds) Distance to Nearest Ephemeral Stream (1) < 100'(Navajo Pits Only) (2) > 100' | | | |
| | TOTAL HAZARD RANKING SCORE:OPOINTS | | | |
| EMAR1. | Remarks: REDUNE E TOPO SHOW LOCATION OUTSIDE V.Z. TWO PITS ON LOCATION. LOCATION DRIP BELONGS TO EPUG. WILL CLOSE PIT | | | |

REMARKS

ORIGINAL PIT LOCATION

- Original Pit : a) Degrees from North 60° Footage from Wellhead 106'
 - b) Length: 16 Width: 13 Depth: 2'



| Remarks | : |
|-------------|---|
| 11011101110 | • |

PHOTOS-1336

Completed By:

Signature

2.22.95

Date

FIELD PIT REMEDIATION/CLOSURE FORM

| GENERAL | Meter: 70992 Location: SAN JUAN 30-6 #99 (PHZ) Coordinates: Letter: M Section 34 Township: 30 Range: 7 Or Latitude Longitude Date Started: 5/2/95 Run: 10 72 |
|--------------------|--|
| FIELD OBSERVATIONS | Sample Number(s): KD 414 Sample Depth: 12' Feet Final PID Reading 753pm PID Reading Depth 12' Feet Yes No Groundwater Encountered Approximate Depth Feet |
| CLOSURE | Remediation Method: Excavation |
| REMARKS | Remarks: Dig fest tok to 12', Took più Sampk, Clased Pit. Signature of Specialist: My Dearn. (SP3191) 03/16/94 |



FIELD SERVICES LABORATORY ANALYTICAL REPORT

PIT CLOSURE PROJECT - Soil Samples Outside the GWV Zone

SAMPLE IDENTIFICATION

| | Field ID | Lab iD | |
|----------------------------|----------|------------------|--|
| SAMPLE NUMBER: | KD414 | 946780 | |
| MTR CODE SITE NAME: | 70992 | N/A | |
| SAMPLE DATE TIME (Hrs): | 5-2-95 | 1345 | |
| SAMPLED BY: | N/A | | |
| DATE OF TPH EXT. ANAL.: | 5-4-95 | 5-4-95 | |
| DATE OF BTEX EXT. ANAL.: | NIA | NID | |
| TYPE DESCRIPTION: | V G | DAMY Reduce Sirl | |

| REMARKS: | |
|----------|--|
| | |

RESULTS

| PARAMETER | RESULT | UNITS | QUALIFIERS | | | |
|----------------|---------|-------|------------|---|------|-------|
| | | | DF | Q | M(g) | V(mi) |
| TPH (418.1) | 30, 100 | MG/KG | | | 137 | 28 |
| HEADSPACE PID | 253 | PPM | | | | |
| PERCENT SOLIDS | 77.3 | % | | | | |

-- TPH is by EPA Method 418.1 --

| larrative: | |
|---------------------|--|
| | |
| Division Franchisco | |

)F = Dilution Factor Used

Approved By: Jalk Date: $\frac{5/7/45}{}$

Test Method for Oil and Grease and Petroleum Hydrocarbons * in Water and Soil * ‡ Perkin-Elmer Model 1600 FT-IR Analysis Report ******************** 35/05/04 11:56 Sample identification -467**8**0 Initial mass of samole. g Volume of sample after extraction, ol 33,000 reproteur hydrocarbons. ppm 19895.cas Tet Besorbance of hydrocarbons (2950 cami) 1810

