OE ()	(Feb. 1951)							

## (SUBMIT IN TRIPLICATE)

## UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Land (	Office	anta.	Je
Lease I	اه	37 <b>34</b> 3x	<u> </u>
T1_14	San	Juna	30-4

## SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT	REPORT OF WATER SHUT-OFF	<b>X</b> .
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT	REPORT OF SHOOTING OF AC	IDIZING
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.	SUBSEQUENT	REPORT OF ALTERING CASHA	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR W	VELLSUBSEQUENT	REPORT OF RE-DRILLING DE	REPAIR
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT	REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENT	ARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL			e centogical \$58V
(INDICATE ABOVE BY	CHECK MARK NATURE OF REPOR		S GEOLOGICAL \$580
	A	gust 1	1960
	(- )	M.H.P.H. (Meridian)	-
•	,		
The elevation of the derrick floor abo	ove sea level is 7405	ft.	
	DETAILS OF WO	RK	
State names of and expected depths to objective say ing poi	nds; show sizes, weights, and le ints, and all other important pr	ngths of proposed casings; ind oposed work)	icate mudding jobs, cement
State names of and expected depths to objective an ing point 7-30-60. Notel Depth 4452 an 141 jts. 5 1/2", J-55, 15. ith 64 sks. reg. commut, 64 seld 1000 # 30 min. op of coment 3970.	ints, and all other important pr	oposta was,	
17-30-60. Notel Depth 4452 20 141 jts. 5 1/2", J-55, 15. 1th 64 sks. reg. cement, 64 s	ints, and all other important pr	oposta was,	
7-30-60. Total Depth 4452 in 141 jts. 5 1/2", J-55, 15. ith 64 sks. reg. comment, 64 s	ensing (4437) the Posmix, 1/4 or	set at \$450 i.ft. Strate-Cret	
17-30-60. Rotal Depth 4452 20 141 jts. 5 1/2", J-55, 15. th 64 sks. reg. coment, 64 s 16 1000 # 30 sdn. up of coment 3970.	the . Possing (4437)	set at \$450 i.ft. Strate-Cret	
I vinderstand that this plan of work must receive the state of the sta	the . Possing (4437)	set at \$450 i.ft. Strate-Cret.	CEIVED  GS 1960  CON. COM.
Tunderstand that this plan of work must receive the standard of the standard o	casing (4437) the Posmix, 1/4 or	set at \$450 i.ft. Strate-Cret.	CEIVED  G S 1960  CON. COM.  DIST: 3