

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.

Use "APPLICATION FOR PERMIT - " for such proposals.

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

ENERGEN RESOURCES CORPORATION

3. Address and Telephone No.

2198 Bloomfield Highway, Farmington, NM 87401

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1263' FNL, 849' FEL, Sec. 29, T30N, R4W, N.M.P.M.

5. Lease Designation and Serial No.

SF-079488A

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

San Juan 30-4 Unit

8. Well Name and No.

San Juan 30-4 Unit 3

9. API Well No.

30-039-07763

10. Field and Pool, or exploratory Area

E. Blanco PC

11. County or Parish, State

Rio Arriba NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☒ Notice of Intent
☐ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☒ Other Deepen. Case. Frac
☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

It is intended to deepen and refrac the Pictured Cliffs as follows:

1. MIRU. TOH with 1 1/4" tubing.
2. Pick up 2 7/8" workstring and packer. Set packer at 3950'. Test casing to 500 psi. TOH.
3. TIH with 6 1/4" bit and drill out to 4400'. Circulate hole clean. TOH.
4. Run 500' 4 1/2" 10.5# casing to 4400'. Cement with 60 sks class B cement.
5. Selectively perforate and fracture Pictured Cliffs.
6. TIH and clean out with air mist. Land tubing at bottom perforation. Return to production.

14. I hereby certify that the foregoing is true and correct

Signed

Title Production Superintendent

Date 5/17/99

(This space for Federal or State office use)

Approved by

/s/ Duane W. Spencer

Title

Team Lead, Production Management

Date

JUN 10 1999

Conditions of approval, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

* See Instruction on Reverse Side

NMOCD