Form	9-3311	
(A pri	11952)	

	•	
 `		
 ļ		

## (SUBMIT IN TRIPLICATE)

## UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Form at	pproved.	
Budget	Bureau No.	. 42-R359.4

dian	Agency . Sicarilla
	Tribal

llettee	
esse No	281

,						מח ת כן
TIGE OF INTENTION TO SEL	, l	X	SUBSEQUENT REPORT OF	WATER SHIIT-OFF	DE (	
TICE OF INTENTION TO DRIL TICE OF INTENTION TO CHAN			SUBSEQUENT REPORT OF		Dizing	
TICE OF INTENTION TO TEST			SUBSEQUENT REPORT OF			G 27 198
TICE OF INTENTION TO REDI			SUBSEQUENT REPORT OF		,	
TICE OF INTENTION TO SHOO			SUBSEQUENT REPORT OF			STOCICAL S'
TICE OF INTENTION TO PULL			SUPPLEMENTARY WELL HI	STORY	U. S. GEO	,
TICE OF INTENTION TO ABAN	IDON WELL				FANNING	1014 1124 11
(IN	DICATE ABOVE BY CHECK MARI	K NATU				
			Aug	ast 23,		., 19. <b>62</b>
Jicarill 1-28		. ]	(N)	(E.)		28
l No1		om	line and 1630	.tt. from	line of co	17.71
(% Sec. and Sec. No.)	(Twp.)	(R	ange) (Me	ridian)	11.12	AED 1
Wildcat	Rio Arrib	-		How N	My Sep	0 1962
(Field)	(Count	y or Su	ıbdivision)	(State or	Colline T	MODELL
alariation of the day	rick floor above sea le	evel	: 8145 <sub>ft</sub>	1		
e elevation of the def	TICK HOOF ABOVE SEA IN	CVCI	1010.		/or 2	DN. COM
1	DETA	ILS	OF WORK			
1		_				obs, cement-
te names of and expected dex	the to objective sands: show a	izes. w	reights, and lengths of prope	Deed Curings; Indie	ate mudding :	
te names of and expected der	oths to objective sands; show a ing points, and all	izes, w other	reights, and lengths of proper important proposed work			
te names of and expected dep	oths to objective sands; show a ing points, and all	to	evaluate the	potentia		
to names of and expected dep (111 a 4500 f (ca of oil fre	the to objective sands; show a ing points, and all recentors test  a possible 2	to	evaluate the			
111 a 4500' @	points, and all reemborn test  a possible	to	evaluate the tured reserv	potentia		
111 a 4500' @	receive sands; show a ing points, and all receives a possible f	to	evaluate the tured reserving and comen	potentis pir: t with 30	l for	produc-
111 a 4500' @	reenhorn test a possible f 1/8" surface o approximate TB	to rac	evaluate the tured reserving and comen's 4500' with	potentis pir; t with 30 pable too	l for	
111 a 4500' @	receiper test  receiper test  a possible f  l/8° surface c  approximate TS  y a protection	to rac	evaluate the tured reserving and comen	potentis pir; t with 30 pable too	l for	produc-
111 a 4500' @	reenhorn test a possible f 1/8" surface o approximate TB	to rac	evaluate the tured reserving and cement 4500' with tring of casing to TD;	potentis pir; t with 30 pable too	l for	produc-
111 a 4500' @	reenborn test  a possible f  No surface o  approximate To  approximate To	to rac	evaluate the tured reserving and comen's 4500' with	potentis pir; t with 30 pable too	l for	produc-
111 a 4500' @	reenborn test  a possible f  No surface o  approximate To  approximate To	to rac	evaluate the tured reserving and cement 4500' with tring of casing to TD;	potentis pir; t with 30 pable too	l for	produc-
set 100' 13 or 100' 13 or 110 to an of oil to an or oil to an or oil to an or oil to an or oil to an oil trans	reenhorn test  a possible f  3/8" surface of approximate TB y a protection hay-Induction ductive, to a being approxim	to rac	evaluate the tured reserving and ement 4500' with tring of casi; to TD; approximatel;	potentia t with 30 cable too y 3500'	l for	produc-
est 100' 13 erill to an erill trace;	reenhorn test  a possible f  3/8" surface o  approximate TS  y a protection  Ray-Induction  eductive, to s	to rac	evaluate the tured reserving and ement 4500' with tring of casi; to TD; approximatel;	potentia t with 30 cable too y 3500'	l for	produc-
set 100' 13 drill to an if necessar run a Gamma indicated pur the 100 sects, and-eil fras; comply with	reenhorn test  a possible f  3/8" surface of approximate TB y a protection hay-Induction ductive, to a being approxim	to rac	evaluate the tured reserving and ement 4500' with tring of casi; to TD; approximatel;	potentia t with 30 cable too y 3500'	l for	produc-
est 100' 13 drill to an of oil to an of oil from a drill to an or oil to an oil to an oil to an oil to an oil from the comply with time tod forms	reenhorn test  a possible f  3/8" surface of approximate TS y a protection tay-Induction eductive, to a hang approximate the rules and	to rac	evaluate the tured reserving and ement 4500' with tring of casi; to TD; approximatel;	potentia t with 30 cable too y 3500'	l for	produc-
set 100' 13 drill to an erill trace and erill trace comply with timeted forms era, 4475'	reenhorn test  a possible f  3/8" surface of approximate TS y a protection tay-Induction eductive, to a hang approximate the rules and	to rac asi oi si lot let	evaluate the tured reserving and cement 4500' with tring of casis to TD; approximately 1000' of pulations of partie, 2190';	potentia pir; t with 36 cable too ng; y 3500' o 4" slette the UUGS Hancos	sacks ols, ca of Sign of line and HM 2640';	roduc- ; rry- casing c and pec. dreen-
set 100' 13 drill to an gif necessari run a Gamma indicated purindent fraction of the comply with timeted forms and 4475' understand that this plan of the comply with the complex that the c	reenhorn test  a possible f  3/8° surface of approximate TB y a protection Ray-Induction beng approximate the rules and tion tops: Ma	to rac asi oi si lot let	evaluate the tured reserving and cement 4500' with tring of casis to TD; approximately 1000' of pulations of partie, 2190';	potentia pir; t with 36 cable too ng; y 3500' o 4" slette the UUGS Hancos	sacks ols, ca of Sign of line and HM 2640';	roduc- ; rry- casing c and pec. dreen-
set 100' 13 drill to an erill trace and erill trace or an er	reenhorn test  a possible f  3/8° surface of approximate TB y a protection Ray-Induction beng approximate the rules and tion tops: Ma	to rac asi oi si lot let	evaluate the tured reserving and cement 4500' with tring of casis to TD; approximately 1000' of pulations of partie, 2190';	potentia pir; t with 36 cable too ng; y 3500' o 4" slette the UUGS Hancos	sacks ols, ca of Sign of line and HM 2640';	roduc- ; rry- casing c and pec. dreen-
set 100' 13 drill to an indicated purished forms with the second state of the second s	reenhorn test  a possible f  3/8° surface of approximate TB y a protection Ray-Induction beng approximate the rules and tion tops: Ma	to rac last log let rec	evaluate the tured reserving and cement 4500' with tring of casis to TD; appreximately 1000' of pulations of pulations of pulations of the tring by the Geological Surving By the By the Geological Surving By the By	potentia pir; t with 36 cable too ng; y 3500' o 4" slette the UUGS Hancos	sacks ols, ca of Sign of line and HM 2640';	roduc- ; rry- casing c and pec. dreen-
est 100' 13 drill to an of oil from of oil from the set 100' 13 drill to an of oil to an oil from the set 100 saches, and	Tremborn test  a possible f  3/8" surface of approximate TS y a protection tay-Induction eductive, to a hang approxim the rules and tion tops: He f work must receive approval	to rac last log let rec	evaluate the tured reserving and cement 4500' with tring of casis to TD; appreximately 1000' of pulations of pulations of pulations of the tring by the Geological Surving By the By the Geological Surving By the By	potentia pir; t with 36 cable too ng; y 3500' o 4" slette the UUGS Hancos	sacks ols, ca of Sign of line and HM 2640';	roduc- ; rry- casing c and pec. dreen-
set 100' 13 et 100' 13 et 100' 13 et 111 to an et 100' 13 et 111 to an et 100' 13 et 111 to an e	Tremborn test  a possible f  3/8" surface of approximate TS y a protection tay-Induction eductive, to a hang approxim the rules and tion tops: He f work must receive approval	to rac last log let rec	evaluate the tured reserving and cement 4500' with tring of casis to TD; appreximately 1000' of pulations of pulations of pulations of the tring by the Geological Surving By the By the Geological Surving By the By	potentia pir; t with 36 cable too ng; y 3500' o 4" slette the UUGS Hancos	sacks ols, ca of Sign of line and HM 2640';	roduc- ; rry- casing c and pec. dreen-
set 100' 13 et 100' 13 et 100' 13 et 111 to an et 100' 13 et 111 to an et 100' 13 et 111 to an e	Tremborn test  a possible f  3/8" surface of approximate TS y a protection tay-Induction eductive, to a hang approxim the rules and tion tops: He f work must receive approval	to rac last log let rec	evaluate the tured reserving and cement 4500' with tring of casis to TD; appreximately 1000' of pulations of pulations of pulations of the tring by the Geological Surving By the By the Geological Surving By the By	potentia pir; t with 36 cable too ng; y 3500' o 4" slette the UUGS Hancos	sacks ols, ca of Sign of line and HM 2640';	roduc- ; rry- casing c and pec. dreen-
act 100' 13 erill to an indicated processes indicated forms of the processes indicated forms indicated forms in 4475' understand that this plan of the processes in the process	Tremborn test  a possible f  3/8" surface of approximate TS y a protection tay-Induction eductive, to a hang approxim the rules and tion tops: He f work must receive approval	to rac last log let rec	evaluate the tured reserving and cement 4500' with tring of casis to TD; appreximately 1000' of pulations of pulations of pulations of the tring by the Geological Surving By the By the Geological Surving By the By	potentia pir; t with 36 cable too ng; y 3500' o 4" slette the UUGS Hancos	sacks ols, ca of Sign of line and HM 2640';	produc- ; rry- casing s and pec. dreen-