



(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Indian Agency **Jicarilla**
Tribal
Allottee _____
Lease No. **Contract 281**

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL		SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF		SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO REDRILL OR REPAIR WELL		SUBSEQUENT REPORT OF REDRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE		SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING		SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL	X		

RECEIVED
FEB 26 1963
U. S. GEOLOGICAL SURVEY
ALBUQUERQUE, NEW MEXICO

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

February 21, 19**63**

Jicarilla-Wirt
Well No. **1-23** is located **630** ft. from **[N]** line and **1650** ft. from **[E]** line of sec. **28**
NE/4 Section 28 **T30N** **R1W** **N4PM**
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Wildcat **Rio Arriba** **New Mexico**
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is **8148** ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

TD 4445' in Graneros sh. Cable tool hole.

Casing: 13 3/8 @ 280' set w/50 sacks, 10 3/4 @ 798 set w/no cement, 8" @ 2385' set w/no cement, 7" @ 2596 set w/no cement, 5 1/2" @ 4367' set w/no cement.

Water sand at 2198'; Gas at 3610', decreased to too small to measure; Gas at 3985', decreased to too small to measure.

To pull all casing except 13 3/8", load hole with heavy mud to 4030', set 100' cement plug 4030' to 3930', load hole with heavy mud to 3660', set 100' cement plug 3660' to 3560', load hole with heavy mud to 2250', set 100' cement plug 2250' to 2150', load hole with heavy mud to 100', set cement plug 100' to surface and erect dry hole marker of 4" pipe.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company **George Parker, Jr.**

Address **2300 Alamo National Bldg.**

San Antonio 5, Texas

By **F. H. Stevens, Jr.**
Agent
2929 Monte Vista N. E.
Albuquerque, New Mexico