

NEW MEXICO ENERGY, MINERALS & NATURAL RESOURCES DEPARTMENT

OIL CONSERVATION DIVISION
AZTEC DISTRICT OFFICE
1000 RIO BRAZOS ROAD
AZTEC NM 87410
(505) 334-4178 FAX: (505) 334-4170
http://emnrd.state.nm.us/ocd/District NV3distric.htm

This form is not to be used for reporting packer leakage tests in Southeast New Mexico

Page 1 Revised 11/16/98

NORTHWEST NEW MEXICO PACKER LEAKAGE TEST

Operator_	Phillips Petr	oleum Co. 0	1765 ⊌ ease Na		្រឹក្ស n Ju		Well No ²⁷	
				19 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	P ! 5 5.0	API# 30-0 ³⁹⁻⁰⁷⁷	-	
	NAME OF RESE		TYPE OF PROD. (Oil or Gas)		METHOD OF PROD. (Flow or Art. Lift)	PROD.MEDIUM (Tbg. or Csg.)		
Upper Completion	Mesaverde		ga	gas		lowing	tubing	
Lower Completion	Dakota	ga	gas f		lowing	tubing		
		PRE-	FLOW SHUT-II	N PRESSU	RE D	ATA		
Upper Completion	Hour, date shut-in 12/4/00			Length of time shut-in 3 days		oress. Psig 495	Stabilized? (Yes or No) yes	
Lower Completion	Hour, date shut-in 12/4/00			Length of time shut-in 3 days		oress. Psig	Stabilized? (Yes or No) yes	
			FLOW TE	ST NO. 1				
Commenced at	(hour, date)*			Zone producir	ng (Upp	er or Lower):	· · · · · · · · · · · · · · · · · · ·	
TIME (hour,date)	LAPSED TIME SINCE	PRES Upper Completion	SURE Lower Completion	PROD ŽO TEMP.		REMARKS		
12/8/00	24 hrs	503	470			Upper SI; flowed lower		
12/9/00	48 hrs	. 508	. 420	-		Upper SI; flowed lwoer		
		_						
roduction ra	ate during test							
Dil:		BOPD base	ed on	Bb s. i	n	Hours	GravGOR	
3as:		MC	FPD; Tested th	ru (Orifice d	or Me	eter):		
		MID-	TEST SHUT-IN	I PRESSUF	RE D	ATA		
Upper Completion	Hour, date shut-in			Length of time shut-in		press psig	Stabilized? (Yes or No)	
Lower Completion	Hour, date shut-in		Length of time shut-in		press. psig	Stabilized? (Yes or No)		
	•	<u></u>	(Continue on	reverse-side)			

FLOW TEST NO. 2

Commence	d at (hour, date)	**	Zone producing (Upper or Lowr):				
TIME (hour,date)	LAPSED TIME Since**		Lower Completion	PROD. ZONE	REMARKS		
							
	te during test) based on	Rb	le in Ua			
as:		MCF	PD:Tested thru	(Orfice or Meter):	oursGravGOR		
emarks:							
nereby certif		nation herein co	ntained is true ar	nd complete to the	e bes of my knowledge.		
oproved w Mexico Oil	I Conservation D				etroleum Company		
	BIOMED BY CHAI		Ву 🔐	im Kenne	dy Jim Kennedy		
			Title	Temporary Wel	/ Ll Tester		
•							

NORTHWEST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- 1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the wellhead pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an Initial
- packer leakage lest, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.
- Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.
- Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test no. 2 is to be the same as for Flow Test No. 1 except

- that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow-period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test date.
- 24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.
- 8. The result s of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico oil Conservation Division on northwest new Mexico packer leakage Test Form Revised 11-16-98 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).