			/
Form 9-331 (May 1963)	UNITED STATES DEPARTMENT OF THE INTERI GEOLOGICAL SURVEY	SUBMIT IN TRIPLICATE* (Other instructions on reverse side)	Form approved. Budget Bureau No. 42-R1424. 5. LEASE DESIGNATION AND SERIAL NO. SF 079489-A
		211110	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
(Do not	SUNDRY NOTICES AND REPORTS C use this form for proposals to drill or to deepen or plug b Use "APPLICATION FOR PERMIT—" for such pr	ON WELLS rack to a different reservoir. roposals.)	
1.			7. UNIT AGREEMENT NAME
WELL	WELL OTHER		San Juan 30-4 Unit
2. NAME OF OPE			8. FARM OR LEASE NAME
El Paso Natural Gas Company 3. ADDRESS OF OPERATOR			San Juan 30-4 Unit
3. ADDRESS OF		71	
4. LOCATION OF See also space	PO Box 990, Farmington, NM 8740 well (Report location clearly and in accordance with any se 17 below.)	2 (P&A) 10. FIELD AND POOL, OR WILDCAT	
At surface 667'N, 833'E			East Blanco Pictured Cliffs 11. SEC., T., R., M., OR ELK. AND SCRVET OR AREA Sec. 19, T-30-N, R-4-W
			NMPM
14. PERMIT NO.	15. ELEVATIONS (Show whether DF,	, RT, GR, etc.)	12. COUNTY OR PARISH 13. STATE
	7512'0	GL	Rio Arriba New Mexico
16.	Check Appropriate Box To Indicate N	lature of Notice, Report, or C	Other Data
	NOTICE OF INTENTION TO:	SUBSEQU	TENT REPORT OF:
**************************************	S SHUT-OFF PULL OR ALTER CASING	WATER SHUT-OFF	REPAIRING WELL
TEST WATER		FRACTURE TREATMENT	ALTERING CASING
SHOOT OR A	Y	SHOOTING OR ACIDIZING	ABANDONMENT*
REPAIR WEL	L CHANGE PLANS	(Other)	of pultiple completion on Well
(Other)		Completion or Recompl	of multiple completion on Well letion Report and Log form.)
17. DESCRIBE PRO proposed nent to the	prosed or completed operations (Clearly state all pertinen work. If well is directionally drilled, give subsurface locat is work.) *	it details, and give pertinent dates, tions and measured and true vertice	including estimated date of starting any al depths for all markers and zones perti-
	Due to non-commerical production,	it is planned to plug	and abandon
	this well in the following manner:	, ,	
	5		
	Spot a 50 sack cement plug to fill	to 4033' and cover pe	rforations (4248-4300').
	Perforate squeeze holes in 7" casin 50 sack cement plug at 3813' and part Alamo outside casing and leave 25	oressure displace 25 s	acks to cover Ojo
	Ojo Alamo.	•	-
	C1	ad mull control Cont	50 good goment
	Shoot off 7" casing at free point an	id pull casing. Spot a	a 50 sack cement 1/11
	plug on the casing stub.		2 OCT 1 0 1074

Spot a 25 sack cement plug at base of the 9 5/8" surface casing OIL CON. COM

Spot a 15 sack cement plug at the surface with a Plug & Abandon may clean up location.

18. I hereby certify that the soperopes is who are correct SIGNED	TITLE Petroleum Engineer	DATEOctober 14, 1971
(This space for Federal or State office use)		
APPROVED BYCONDITIONS OF APPROVAL, IF ANY:	TITLE	DATE