



(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office Santa Fe
Lease No. 078741
Unit San Juan 30-6 Unit
14-08-001-538

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	SUBSEQUENT REPORT OF WATER SHUT-OFF.....	<input checked="" type="checkbox"/>
NOTICE OF INTENTION TO CHANGE PLANS.....	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....	<input type="checkbox"/>
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....	SUBSEQUENT REPORT OF ALTERING CASING.....	<input type="checkbox"/>
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.....	<input type="checkbox"/>
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....	SUBSEQUENT REPORT OF ABANDONMENT.....	<input type="checkbox"/>
NOTICE OF INTENTION TO PULL OR ALTER CASING.....	SUPPLEMENTARY WELL HISTORY.....	<input type="checkbox"/>
NOTICE OF INTENTION TO ABANDON WELL.....		<input type="checkbox"/>

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

November 30, 1960, 19__

Well No. 35-24 is located 1060 ft. from N line and 850 ft. from E line of sec. 24

NE Sec. 24 30-N 6-W N.M.P.M.
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Blanco Mesa Verde Rio Arriba New Mexico
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 6305 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudlogging jobs, cementing points, and all other important proposed work)

Spud date 9-4-60, on 9-5-60 Total Depth 300'.
Ran 7 joints 10 3/4", 32.75 # Armo S.W. casing (202') set at 294' w/340 sks.
reg. cement & 2 % calcium chloride circulated to surface. Held 600 # 30 minutes.

On 9-12-60, Total Depth 3483'.
Ran 87 joints 7", 23 # & 20 #, J-55 casing (3472') set at 3482 w/110 sks. reg.
cement, 1/4 cu.ft. Strata-Crete "6"/sk., 2 % calcium chloride. Held 1500 #/30 min.

On 9-19-60 Total Depth 5697'.
Ran 183 joints 2 7/8", 6.4 # J-55 casing (5671') set at 5682' w/160 sks. reg.
cement, 4 % Gel, 1/4 cu.ft. fine Gilsomite/sk., 1/8 # Floccs/sk.
Held 1500 #/30 minutes. Top of cement by temperature survey at 3800'.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company El Paso Natural Gas Company

Address Box 990

Farmington, New Mexico

By ORIGINAL SIGNED H.E. McANALLY

Title Petroleum Engineer