


NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

~~Wagon~~

WELL RECORD

Mail to District Office, Oil Conservation Commission, to which Form C-101 was sent not later than twenty days after completion of well. Follow instructions in Rules and Regulations of the Commission. Submit in QUINTUPLICATE. If State Land submit 6 Copies



~~Blackwood & Mohale Company~~
(Company or Operator)

~~Blackwood & Mohale Unit~~
(Unit)

Well No. 10-16, in SW 1/4 of SW 1/4, of Sec. 16, T. 30N, R. 7W, NMPM.

Blanco Mesquero Pool, Rio Arriba County.

Well is 990 feet from South line and 990 feet from West line of Section 16. If State Land the Oil and Gas Lease No. is 2-178-1

~~Wagon~~ Commenced April 24, 1958 ~~Wagon~~ Completed May 3, 1958

Name of Drilling Contractor J. G. Roberts Drilling, Inc.

Address P.O. Box 636, Artes, New Mexico

Elevation above sea level at Top of Tubing Head 6250' The information given is to be kept confidential until _____, 19____


OIL SANDS OR ZONES

No. 1, from 2915' to 3135' (Gas) No. 4, from 3042' to 3150' (Gas)
No. 2, from 3135' to 3330' (Gas) No. 5, from 3150' to 3492' (Gas)
No. 3, from 3004' to 3042' (Gas) No. 6, from _____ to _____

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from _____ to _____ feet.
No. 2, from _____ to _____ feet.
No. 3, from _____ to _____ feet.
No. 4, from _____ to _____ feet.



CASING RECORD

SIZE	WEIGHT PER FOOT	NEW OR USED	AMOUNT	KIND OF SHOE	CUT AND PULLED FROM	PERFORATIONS	PURPOSE
10-3/4"	38.756	New	213'	Guide	- -		Surface
7"	236	New	981'		- -		Production
7"	208	New	3966'	Float	- -		"
5"	136	New	769'	Guide	- -	3009'-3492'	Liner

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
15"	10-3/4"	224'	200	Pump & Plug	Water	Cement Circulated
8-3/4 7"		4937'	200	" "		Top cement @ 3160'
6-1/4 5"		3534'	300	" "		

RECORD OF PRODUCTION AND STIMULATION

(Record the Process used, No. of Qts. or Gals. used, interval treated or shot.)

Perforated the Point Lookout & Mesquero Zones thru 5" liner with 2 holes per foot & the Cliffhouse Zone with 4 holes per foot. Sand-water flood in 2 stages: 1st stage, 3304'-3492' with 30,600 gal of water (incl. flush) & 32,000 lbs of sand; 2nd stage, 3009'-3130' with 36,196 gal of water (incl. flush) & 40,000 lbs of sand.

Result of Production Stimulation. On 5-21-58, calculated absolute potential was 7,967 MCFD. Rate of flow thru 3/4" choke after 3 hours was 3,604 MCFD

Depth Cleaned Out 3500' FWD