NEW MEXICO OIL CONSERVATION COMMISSION

Form C-122

Revised 12-1-55

MULTI-POINT BACK PRESSURE TEST FOR GAS WELLS

	1 <u>R1</u>											
Ini	tial		Annu	al		Spe	cial		Date of	Test_6	-17-57	
Com	pany Pacifi	c Nort	hvest	Pipeli	ne Corp.	Lease_	San Juan	30-5	We	11 No.j	19-18	
Jni	t <u>G</u>	Sec. 1	8 _Tw	р. <u>30</u>	R _e	ge 5	W_Pur	chaser	Not Con	sected		
	ing 54											
											25. <u>12</u>	
	lucing Thru						x	Type W	ell Singl	•		
							זוה	10 I P K 12 / 1	enneadli	1: 030	G.O. Dual	
							VED DATA					
est	ed Through	(PH)	Heles (Choke)	(MHHH)			7 dave	Тугое Таз	0.5		
			low Da			· 		Data				
T	(Prover)	(Cho	oke)	Press	Diff.	Temp.	Press.	Temp.	Press.	Temp.	Duratio	
	(Line) Size	Si	ice) ize	psig	h	°F.	psig	o _F	psig) JF	of Flo	
					<u> </u>		885	 	1137		111	
•		3/4		270		430	270	430	660		3	
		 					-	 	-		3	
.								<u> </u>		†		
) ·	(24-Hour)		$\sqrt{h_{W}p_{f}}$		psia	Flow Temp. Factor Ft		Factor Fg	Factor Q-MCFPD			
十	12.3650				292 1.0		68	-9608	1.032		351.6	
												
Li vit	iquid Hydrod y of Liquid	d Hydro	ocarbo	ns_ _e ^{-s})		CSSURE C.cf/bbl.deg.		Speci Speci	fic Gravi fic Gravi	ty Flow	rator Gas_ ing Fluid	
								809	2 2			
1	P _w	$P_{\mathbf{t}}^2$	Fc	2	$(F_{cQ})^2$	(F.	$\begin{pmatrix} Q \end{pmatrix}^2 \\ -e^{-s} \end{pmatrix}$	P _w 2	$P_c^2 - P_w^2$	Ca.		
 -		Pt ²	Fc	5	(F _c Q) ²	(F ₁	cQ) ² -e ^{-s})	P _w 2	P _C -P _W	P,		
1		Pt ²	Fc	2	(F _c Q) ²	(F.	cQ) ² -e-s)	P _w 2			P _C	
•		Pt ²	Fc	5	(F _c Q) ²	(F. (1:	cQ) ² -e-s)	804.6			P _C	
sol MPA DRE		al:	7,115		Corper	MCFPD;	n75/				P _C	
sol MPA DRE	Pt (psia) ute Porenti NY Pacific SS Les 1 N and TITLE SSED	al:	7,115		Corper	MCFPD;	n75/				2.56	

INSTRUCTIONS

This form is to be used for reporting multi-point back pressure tests on gas wells in the State, except those on which special orders are applicable. Three copies of this form and the back pressure curve shall be filed with the Commission at Box 871, Santa Fe.

The log log paper used for plotting the back pressure curve shall be of at least three inch cycles.

NOMENCLATURE

- Q = Actual rate of flow at end of flow period at W. H. working pressure ($P_{\rm W}$). MCF/da. @ 15.025 psia and 60° F.
- P_c = 72 hour wellhead shut-in casing (or tubing) pressure whichever is greater. psia
- Pw Static wellhead working pressure as determined at the end of flow period. (Casing if flowing thru tubing, tubing if flowing thru casing.) psia
- Pt Flowing wellhead pressure (tubing if flowing through tubing, casing if flowing through casing.) psia
- Pf Meter pressure, psia.
- hw Differential meter pressure, inches water.
- F_g : Gravity correction factor.
- Ft Flowing temperature correction factor.
- F_{pv} Supercompressability factor.
- n I Slope of back pressure curve.

Note: If $P_{\rm W}$ cannot be taken because of manner of completion or condition of well, then $P_{\rm W}$ must be calculated by adding the pressure drop due to friction within the flow string to $P_{\rm t}$.

OIL CONSERVATION COMMISSION

AZTEC DISTRICT OFFICE

No. Copies Received 3

DISTRIBUTION

NO.

CARRIED

Operator

Santa Fe

Proration Office

State Land Office

U. S. G. S.

Transporter