NEW MEXICO OIL CONSERVATION COMMISSION

Form C-122
Revised 12-1-55

MULTI-POINT BACK PRESSURE TEST FOR GAS WELLS

Poc	ol B	anco			F	ormation	Mesa.	Verde		County_	Rio Ar	riba	
Ini	tial_	xx	·- <u>·</u>	Annu	al		Spec	ial		Date of	Test	9-25-57	
Con	pany P	cific	North	west I	ipelin		Lease_S	an Juan	30-5	Wel	Ll No	20-8	
Uni	t <u>H</u>		Sec	8 Tw	p	30N Rg	ge 5 W	Puro	haser_	t connect	ed		
Cas	7-5/	.} " ₩	/t	I	.D.	Se	3459 et at 575	9 D Pe	rf. 53	18	То	5724	
												ess. 12	
Pro	aucing	īņru:	(a)	sing	X	Tu	ionng	Sir	Type we gle-Brade	ell si	G. or (G.O. Dual	
Dat	e of C	omplet	ion:_			Packe	r		Reserve	oir Temp.			
							OBSERV	ED DATA					
Tes	ted Th	rough	6Boo	((Choke)	(Meber)	shu	t in 19	iays	Type Tap	os		
			I	Flow Da	ata	,		Tubing	Data	Casing I	ata	T	
No.	(Pr	over) ine)	(Cho	oke) fice)	Press. psig	Diff.	,		1	Press.	1	l of Flow	
_	S	ize	S:	ize	psig	h _w	°F.		°F.		°F∙	Hr.	
SI 1.		<u>-</u> ·	3/	4"	258		63	1230 323		1230 258	62	3 hours	
2.										2,0	103	3 2000	
<u>3.</u>			1				<u>'</u>		 	 	 	1	
<u>4.</u> <u>5.</u>											<u> </u>		
							FLOW CAL	CULATION	S				
	Coefficient (24-Hour)		ent		Pr			Temp.	Gravity	Compre	ss.	Rate of Flow Q-MCFPD @ 15.025 psia	
No.			¬ h _w r	h.pe		rac F	tor t	Factor F _g	Factor F _{pv}	r			
1.	12.3650		γ - ων		270		•9971		•9608	1.026		3282	
1. 2. 3.													
4.													
4. 5.													
						PR	ESSURE C	ALCU ATI	ONS				
Gas I	Liquid	Hydro	carbor	n Ratio	,		cf/bbl.		Speci	fic Gravi	t.v. Sena	arator Gas	
Gas Liquid Hydrocarbon Ratio Gravity of Liquid Hydrocarbons						deg.	deg. Spe			ty Flow	ving Fluid		
[?] c	fc(1-e ⁻			L-e ^{-s})_	s)				1242 Pc 1542.6				
										·		····	
No.	$P_{\mathbf{w}}$		P . 2	Fc	Q	$(F_cQ)^2$	(F	-0)2	335 P _w 2	$P_c^2 - P_w^2$	Ca	ıl. Pu	
	Pt (r	sia)		, ,	;		(1	c ^{Q)²} -e ^{-s})	- w	C - w	I	Pw Pc	
1.									12.2	1430.4		1.08	
1. 2. 3. 4. 5.			·									<u>i</u>	
4.											 		
	olute I	Por ent	ial•		3477		MCPPD.	<u></u>	75 / 1.0	rol.			
COME	PANY_P	acifie	Mort.	hwest	Pipeli	ae Corne	ration		13 / T 18	2 94			
ADDF	RESS_4C	万字 Wes	it Bro	edvey,	Parmi	agton, I	iew Mexic rt Engine	<u> </u>					
WITN	VESSED_	111110		H. HING	ner -	Tel Tel	tt isngine	er			- Carrier	* 9 (3 a)	
COM	PANY						DEM	ADVO			(RI	9.0	
							K.E.M.	ARKS		/	300	ulli	
											$^{ u arphi arphi}_{oldsymbol{1}}$	1957	
										1	air COI	V. COM	
										•	nis.	957 V. COM T. 3	

INSTRUCTIONS

This form is to be used for reporting multi-point back pressure tests on gas wells in the State, except those on which special orders are applicable. Three copies of this form and the back pressure curve shall be filed with the Commission at Box 871, Santa Fe.

The log log paper used for plotting the back pressure curve shall be of at least three inch cycles.

NOMENCLATURE

- Q \equiv Actual rate of flow at end of flow period at W. H. working pressure (P_W). MCF/da. @ 15.025 psia and 60° F.
- P_c 72 hour wellhead shut-in casing (or tubing) pressure whichever is greater. psia
- PwI Static wellhead working pressure as determined at the end of flow period. (Casing if flowing thru tubing, tubing if flowing thru casing.) psia
- Pt Flowing wellhead pressure (tubing if flowing through tubing, casing if flowing through casing.) psia
- P_{f} Meter pressure, psia.
- hw- Differential meter pressure, inches water.
- F_g I Gravity correction factor.
- F_t Flowing temperature correction factor.
- Fpv Supercompressability factor.
- n I Slope of back pressure curve.

Note: If $P_{\rm W}$ cannot be taken because of manner of completion or condition of well, then $P_{\rm W}$ must be calculated by adding the pressure drop due to friction within the flow string to $P_{\rm t}$.

AZTSO	DIST	BICT	OFF	CE	
No. Copies A	(erg. <u>11</u>	ved	2		
(3)	3 i Ad	3.77:	- Oto		
		· ·	. 5.	.	-
Operator	•			1.	
santa Fe		1	1		-
rroration littles	-				
State Land Offic	w ,				
U. S. G. S.			7		•
Transporter					*
FILE			/		L

