Form 9-331 (May 1963)	_	NITED STATES		UEMIT IN TRIPLICATES Other instructions on re-	Form approved. Budget Bureau N		
		DEPARTMENT OF THE INTERIOR (COLOR and			5. LEASE DESIGNATION AND SERIAL NO.		
GEOLOGICAL SURVEY					NM 4455		
S	UNDRY NOTIC	ES AND REPO	ORTS ON	WELLS	4. IP INDIAN, ALLOTTES OR	TRIBE WAME	
	this form for proposals Use "APPLICATI						
OIL GA	S.L. XX OTHER		÷		7. UNIT AGRESMENT NAME		
2. NAME OF OPERAT			 		8. FARM OR LEASE HAME		
LONG CTAE	INDUCTRIC	TNC		essi.	SCHALK 55		
3. ADDRESS OF OPE	INDUSTRIES		 	4.70.	9. WELL NO.		
P O ROY		E. SCHALK INGTON, NEW	MEVIO	074.01	2		
4. LOCATION OF WEL	L (Report location clea	rly and in accordance	with any State	dureness.	10. PIELD AND POOL, OR WIL	LDCAT	
See also space 1: At surface	/ below.)			No. of the second	DI ANCO MECA	VEDDE	
0001 5004	L THE MODELL	. TNE 11001	EDOM TI	F 5467 LTNF	BLANCO MESA		
980 FROM	I THE NORTH	LINE, 1180'	FRUM IH	E EAST LINE	SURVEY OR AREA		
					SEC. 3, T-30N	. R-5W	
14. PERMIT NO.		15. ELEVATIONS (Show whether DF, RT, GR, etc.)			12. COUNTY OR PARISH 18.		
<u> </u>	6486' GR				RIO ARRIBA NE	W MEXIC	
16.	Check Appr	opriate Box To Indi	licate Nature	of Notice, Report, or C	Other Data	_	
NOTICE OF INTENTION TO:				SUBSEQUENT REPORT OF:			
TEST WATER SH	UT-OFF PUL	L OR ALTER CASING		WATER SHUT-OFF	REPAIRING WELL		
FRACTURE TREAT		LTIPLE COMPLETE		FRACTURE TREATMENT	ALTERING CASING		
вноот эк астои	E ABA	ANDON*	_	SHOOTING OR ACIDIZING	ABANDON MENT [®]		
REPAIR WELL	CHA	ANGE PLANS		(Other) WELL		X	
(Other)	(Other) (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)						
17. DESCRIBE PROPOSI proposed work nent to this wo	. If well is directional	rions (Clearly state all lly drilled, give subsurf	pertinent detail face locations an	s, and give pertinent dates, d measured and true vertica	including estimated date of all depths for all markers and	starting any sones perti-	
						:	
SCHALK 5	5 WELL NO.	2	SPUDDED	AT 11:00 PM 0	N 8-7-74		

8-24-74

TOTAL DEPTH 5975'

RAN 181 JOINTS OF 4-1/2" 10.50# CASING (62 JOINTS OF K55 + 119 JOINTS OF H-40) TOTALING 5990'. SET AT 5975'. D.V. TOOL SET AT 1986' AND 3991'. FLOAT SET AT 5942'. CEMENTED FIRST STAGE WITH 160 SACKS 50/50 POSMIX WITH 12-1/2# GILSONITE PER SACK AND 125 SACKS OF HALLIBURTON LIGHTWEIGHT WITH 12% GEL AND 12-1/2# GILSONITE AND 1/4# FLOSEAL PER SACK. CEMENTED SECOND STAGE WITH 275 SACKS HALLIBURTON LIGHTWEIGHT WITH 12% GEL, 12-1/2# GILSONITE, AND 1/4 FLOSEAL PER SACK. CEMENTED THIRD STAGE WITH 265 SACKS OF HALLIBURTON LIGHTWEIGHT WITH 12% GEL, 12-1/4# GILSONITE, AND 1/4# FLOSEAL PER SACK. PLUG DOWN AT 10:25 AM. CIRCULATED WITH GOOD RETURNS.

18. I hereby certify that t	of forboings true and fret	Mark AGENT	DATE 8-28-7	
SIGNOD or Feder		MITLE AGENT	DATE 0-26-7	
APPROVED BY		ritle	DATE	