

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

SF 078739

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER		7. UNIT AGREEMENT NAME San Juan 30-5 Unit
2. NAME OF OPERATOR Northwest Pipeline Corporation		8. FARM OR LEASE NAME San Juan 30-5 Unit
3. ADDRESS OF OPERATOR P.O. Box 90, Farmington, New Mexico 87401		9. WELL NO. 56
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 820' FSL & 860' FWL		10. FIELD AND POOL, OR WILDCAT Blanco Mesa Verde
14. PERMIT NO.		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 22, T30N, R5W
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 6454' GR		12. COUNTY OR PARISH Rio Arriba
		13. STATE N.M.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)



17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

12-17-76 Drilled 8 1/4" hole to 3722' w/mud. Ran 3709', 7", 20#, K-55 csg. set at 3722'. Cemented w/100 sks. 65/35 poz w/12% gel followed by 50 sks. Cl. "B" w/2% CC.

12-22-76 Drilled 6 1/4" hole to T.D. of 5806' w/gas. Ran GR-Induction and Density logs. Ran 2252', 4 1/2", 11.6#, K-55 csg. liner set from 3552' to 5804'. FC at 5771'. Cemented w/210 sks. Cl. "B" w/4% gel and 1/4 cu. ft. Gilsonite/sk.

12-23-76 Cleaned out to 5749' and tested csg. to 3500 PSI, held OK. Spotted 500 gal. 7 1/2% HCl. Ran GR-CCl and perfed from 5352' to 5734' w/17 shots. Pumped 1000 gal 7 1/2% HCl w/35 ball sealers. Fraced w/70,000 gal water and 60,000 # 20/40 sand.

12-28-76 Landed 5619' to 2 3/8", 4.7#, J-55, LUE tubing at 5629'. Shut well in for test.



18. I hereby certify that the foregoing is true and correct

SIGNED

D. H. Maroncelli
D. H. Maroncelli

TITLE Production Engineer

DATE 12-29-76

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side