UNITED STATES DEPARTMENT OF THE INTERIOR

D		_	. 1
- 14	evi	c	24

Form 9-331 Dec. 1973	Form Approved. Budget Bureau No. 42-R1424			
UNITED STATES	5. LEASE			
DEPARTMENT OF THE INTERIOR	SF 080712-A			
sed Copy. GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME			
SUNDRY NOTICES AND REPORTS ON WELLS	7. UNIT AGREEMENT NAME			
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)	San Juan 30-6 Unit			
	8. FARM OR LEASE NAME			
1. oil gas well other	San Juan 30-6 Unit			
2. NAME OF OPERATOR	9. WELL NO.			
El Paso Natural Gas Company	54A			
	10. FIELD OR WILDCAT NAME			
3. ADDRESS OF OPERATOR Pox 280 Formington Nov. Marriag. 07401	Blanco Mesa Verde			
Box 289, Farmington, New Mexico 87401	11. SEC., T., R., M., OR BLK. AND SURVEY OR			
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	AREA Sec. 21, T-30-N, R-6-W			
below.) AT SURFACE: 1800'S, 1720'E	N.M.P.M.			
AT TOP PROD. INTERVAL:	12. COUNTY OR PARISH 13. STATE			
AT TOTAL DEPTH:	Rio Arriba New Mexico			
	14. API NO.			
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,				
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD)			
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF	6385' G1			
TEST WATER SHUT-OFF FRACTURE TREAT FRACTURE TREAT				
SHOOT OR ACIDIZE				
REPAIR WELL	(NOTE D			
PULL OR ALTER CASING	(NOTE: Report results of multiple completion or zone change on Form 9-330.)			
MULTIPLE COMPLETE				
CHANGE ZONES 🗍 🦷				
ABANDON*				
(other)	en e			
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state				

10 may 10

A 15.00

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly s including estimated date of starting any proposed work. If well is measured and true vertical depths for all markers and zones pertinent to this work.)

TD 6029'. Left Gamma-Ray Density Logging Tool with Radioactive Source in hole.)-18-79: Spotted cement with red dye across and above tool. Ran Deflector tool on bottom of liner. Ran 77 joints 4 1/2", 10.5#, K-55 casing liner 2467' set 3510-5978'. Float collar set at 5961'. Cemented w/ 431 cu. ft. cement. WOC 18 hours. Will provide sketch of hole conditions after completion.

Subsurface Safety Valve: Manu. and Type				Set @ Ft.		
18. I hereby certify that the foregoing is tri	No. of the second second					
SIGNED S. D. Brisco	TITLE Drilling	Clerk DATE _	October	31, 1979		
	(This space for Federal or Stat	te office use)				
APPROVED BY	TITLE	DATE				