

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other ☐
2. NAME OF OPERATOR
SCHALK DEVELOPMENT CO.
3. ADDRESS OF OPERATOR
P. O. BOX 25825/ ALBUQ., NM 87125
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) 986' FNL; 1660' FWL
AT SURFACE:
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:		SUBSEQUENT REPORT OF:
TEST WATER SHUT-OFF	<input type="checkbox"/>	<input type="checkbox"/>
FRACTURE TREAT	<input type="checkbox"/>	<input type="checkbox"/>
SHOOT OR ACIDIZE	<input type="checkbox"/>	<input type="checkbox"/>
REPAIR WELL	<input type="checkbox"/>	<input type="checkbox"/>
PULL OR ALTER CASING	<input type="checkbox"/>	<input type="checkbox"/>
MULTIPLE COMPLETE	<input type="checkbox"/>	<input type="checkbox"/>
CHANGE ZONES	<input type="checkbox"/>	<input type="checkbox"/>
ABANDON*	<input type="checkbox"/>	<input type="checkbox"/>
(other) DRILLING	XXX	XXX


5. LEASE NM 4457
6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
Schalk 57
9. WELL NO.
#2A
10. FIELD OR WILDCAT NAME
Blanco Mesa Verde
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 12, T-30N, R-5W
12. COUNTY OR PARISH
Rio Arriba,
13. STATE
New Mexico
14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
6589'

(NOTE: Report results of multiple completion or zone change on Form 9-331.0.)



17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

11/11/80 Spud and Drill 12-1/4" Hole to 308'.
Ran 7 jnts (292.92') of 8-5/8" 32# surface casing set @ 308' KBM. Cemented with 210 sxs Class 'B' w/2% c.c. Cement circulated to surface. Plud down @ 2:15 a.m.
11/16/80 Dilling 7-7/8" Hole @ approx. 3605'.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED [Signature] TITLE Mng. Partner DATE 12/24/80

ACCEPTED FOR RECORD (space for Federal or State office use)

APPROVED BY [Signature] DATE JAN 08 1981 TITLE _____ DATE _____

CONDITIONS OF APPROVAL IF ANY:

BY [Signature] FARMINGTON DISTRICT