Form 3160-5 (November 1983) (Formerly 9-331)  UNITED STATES SUBMIT IN TRIPLICATE* (Other instructions on re-		Form approved. Budget Bureau No. 1004-0135 Expires August 31, 1985  5. LEASE DESIGNATION AND SERIAL NO.	
BUREAU OF LAND MANAGE	_· <del>-</del>	Jicarilla Con	
SUNDRY NOTICES AND REPORTS ON WELLS		6. IF INDIAN, ALLOTTES OR THIS NAME	
(Do not use this form for proposals to drill or to deepen or Use "APPLICATION FOR PERMIT —" for	plug back to a different reservoir.	Jicarilla Apa	che Trib
I. OIL GAS X OTHER		7. UNIT AGREEMENT HAM	
2. NAME OF OPERATOR Robert L. Bayless		8. FARM OR LEASE NAME	<del> </del>
ADDRESS OF OPERATOR		Jicarilla 460	
P.O. Box 168, Farmington, NM 87499	RECEIVED	9. WELL NO.	
<ol> <li>LOCATION OF WELL (Report location clearly and in accordance with See also space 17 below.)</li> <li>At surface</li> </ol>	JAN 06 1987		
7001 EGT 6 0001 EUE		11. SEC., T., R., M., OR BLE. AND	
790' FSL & 890' FWL	BUREAU OF LAND MANAGEMENT FARMINGTON RESOURCE AREA	JREAU OF LAND MANAGEMENT ARMINGTON RESOURCE AREA Sec. 21, T30N, R3W	
4. PERMIT NO. 15. SLEVATIONS (Show wheth		12. COUNTY OR PARISH 1	
7191 GL	7203 RKB	Rio Arriba	NM
	ie Nature of Notice, Report, or O	ther Data	
NOTICE OF INTENTION TO:	EUDRBRUS	QUENT REPORT OF:	
TEST WATER SHUT-OFF PULL OR ALTER CASING	WATER SHUT-OFF	REPAIRING WEL	L
PRACTURE TREAT MULTIPLE COMPLETE	FRACTURE TREATMENT	ALTERING CASI:	1a
SHOOT OR ACIDIZE ABANDON®	SHOOTING OR ACIDIZING	*THEW HOOMAGA	
REPAIR WELL CHANGE PLANS	(Other) TD; log; se (Nors: Report results of		
per attached daily re	eport.		
		Mr. Marie	
		JAN 13.	
	(	DIL CON DIN	
		JAN 13 1987 CON. DIV	
I hereby certify that the foregoing in those and correct SIGNED	Petroleum Engineer	OIL CON. DIV.  DIST. 3  01/05	6/87
SIGNED		01/05	
SIGNED LLUM H. M. COW TITLE		DATE 01/05	

\*See Instructions on Reverse Side

FARMINGTON RESOURCE AREA
BY 693

## ROBERT L. BAYLESS

PETROLEUM PLAZA BUILDING
P. O. BOX 168
FARIMINGTON, NEW MEXICO 87499
1505) 326-2659

## DAILY REPORT

Jicarilla 460 #2
790' FSL & 890' FWL
Sec. 21, T30N, R3W
Rio Arriba County, New Mexico

1/4/87 TD well at 4115' RKB at 6:00 a.m. 1/4/87. Circulate for logs.

1/5/87

Circulate for 1 hr. Short trip (no fill); circulate for 1-1/2 hrs; TOH for logs. Rigged up Welex; ran IEL, CNL-FDC logs from loggers TD of 4112' RKB to surface. Tripped in hole with drillpipe and collars; laydown drillpipe and collars; ran 4-1/2" casing and landed as follows:

DESCRIPTION	LENGTH	DEPTH
KB to landing point 96 jts. of 4-1/2" 11.6#/ft. J-55 new	12.00	0-12
casing (Korean Pusan) 1 DFFC 1 jt. of 4-1/2" 11.6#/ft. J-55 new	4046.17 2.25	12-4058 4058-4060
casing Shoe Joint l cement filled guide shoe	$\begin{array}{r} 42.20 \\ \underline{1.00} \\ 4103.62 \end{array}$	4060-4103 4103-4104

Centralizers @ 4082, 3974, 3805, 3763, 3721, and 3637.

Rigged up Dowell and pumped 5 bbls. of water ahead. Cemented casing with 225 sacks (284 ft. $^3$ ) of 50/50 pozmix w/2% gel, 10% salt. Good circulation throughout job. Bumped plug to 1250 psi. Plug down @ 10:15 p.m. on 1/4/87. Set slips and release rig. Ran temperature survey. Top of cement @ 2700 ft. RKB. Wait on completion.