30-039-25409

Revised 10.01/78

Page 1

OIL CONSERVATION DIVISION

STATE OF NEW MEXICO ENERGY and MINERALS DEPARTMENT

> This form is not to be used for reporting packer leakage tests in Southeast New Mexico

NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

Well 92A No. SAN JUAN 30-6 UNIT BURLINGTON RESOURCES OIL & GAS CO. Lease Operator Location **RIO ARRIBA** County 007W Rge. 030N 33 Twp. of Well: Unit Sect METHOD OF PROD. PROD. MEDIUM TYPE OF PROD. NAME OF RESERVOIR OR POOL (Flow or Art. Lift) (Tbg. or Csg.) (Oil or Gas) Tubing Artificial Gas Upper PICTURED CLIFFS Completion Tubing Artificial Lower Gas **MESAVERDE** Completion PRE-FLOW SHUT-IN PRESSURE DATA Stabilized? (Yes or No) SI press. psig Length of time shut-in Hour, date shut-in Upper 288 72 Hours Completion 09/28/2001 Lower 199 120 Hours Completion 09/28/2001 FLOW TEST NO. 1 UPPER Zone producing (Upper or Lower) 10/01/2001 Commenced at (hour.date)* PROD. ZONE **PRESSURE** LAPSED TIME TIME REMARKS TEMP Upper Completion Lower Completion SINCE* (hour.date) PC. Csg. Psi - 313 199 117 96 Hours 10/02/2001 PC. Csg. Psi - 193 199 117 120 Hours 10/03/2001 PC. Csg. Psi - 147 Production rate during test GOR Gray. Hours. BOPD based on Oil MCFPD: Tested thru (Orifice or Meter): Gas: MID-TEST SHUT-IN PRESSURE DATA Stabilized? (Yes or No) SI press. psig Length of time shut-in Hour, date shut-in Upper Completion Stabilized? (Yes or No) SI press, psig Length of time shut-in Hour, date shut-in Lower Completion (Continue on reverse side) 3578702 346

FLOW TEST NO. 2

TIME LAPSED TIME DEFOUND				Zone producing (Upper or Lower):		
(hour, date)	LAPSED TIME SINCE **	PRESSURE		PROD. ZONE		
		Upper Completion	Lower Completion	TÉMP.	REMARKS	
		 				
			 	 		
						
narks:		MCFPD	: Tested thru (Orific	e or Meter):		
reby certify that	the information here	in contained is true a	and complete to the h	pest of my knowledge		
ravad	001167	2007	·	moviedge.		
pproved			Op	Operator Burlington Resources		
vew Mexico Oil	Conservation Divisi	on		110	4	
			By	Moro Ula	%	
	\					
GFR6N/	IT SIGNED BY OHN	PLIE T. PERMISA			0	
	A CHE ST PYS INDE	PALE T. PERMAN	Tit	le Operations Assoc	iate	
GFREIN				de <u>Operations Assoc</u>		

NORTHWEST NEWMEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- A packer le ikage test shall be commenced on each multiply completed well within A spector is taget ext small occommended on each manager completed with a seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division
- At least 723 ours prior to the commencement of any packer leakage test, the operator shall notify the D vision in writing of the exact time the test is to be commenced. Offset operators shall also be so notified
- The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more
- 4 For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note, if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to lack of a pipeline connectio : the flow period shail be three hours.
- Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above
- Flow Test $N\varepsilon/2$ shall be conducted even though no leak was indicated during Flow Test No. 1 Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except

- that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.
- Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows 3 hours tests immediately prior to the beginning of each flow period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data
- 24-hour oil zone tests all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.
- 8 The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only)