

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)

Budget Bureau No. 1004-0135
Expires August 31, 1985

5. LEASE DESIGNATION AND SERIAL NO.

SF - 079486

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Simms Com

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

East Blanco Pictured Cliffs

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 28, T30N, R4W

12. COUNTY OR PARISH 13. STATE

Rio Arriba

NM

1. OIL ☐ GAS ☒ OTHER ☐

2. NAME OF OPERATOR

McElvain Oil & Gas Properties, Inc.

3. ADDRESS OF OPERATOR

P.O. Box 2148, Santa Fe, NM 87504-2148

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface

989' FNL & 851' FWL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, CR, etc.)

7444 GR

RECEIVED
MAY - 6 1986

OIL CON. DIV.

DIST. 2

16. Check Appropriate Box To Indicate Nature of Notice Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANE

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Set Production Casing

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

April 21, 1996

Ran 104 jts.; 10.5#, J-55, ST&C casing with cement nose guide shoe on bottom. Self-fill insert float valve one joint up. DV tool 14 joints up. 4488.23' of casing set at 4503' KB. Float at 4459' KB. DV tool at 3894' KB. Regular centralizers at 4481', 4459', 4416', 4329', 4242', 4156', 4070', 3983', 3940', 3851', 3678', 3635' & 3548'. Turbolizers at 3808', 3746', & 3721'. Land casing in mandrel hanger. Cement first stage with 180 sxs Class B with 1/4# celloflake/sk. PD @ 11:30am.

Opened DV tool. Circulate and WOC 4 hours. Cement second stage with 695 sxs ThriftyLite 2 followed by 100 sxs Class B. Both slurries contained 1/4# celloflake/sk. Circulated 9 bbls. of 12.0 ppg slurry to surface.

Plug down at 5:00pm, 4/21/96. Release rig at 6:00pm, 4/21/96.

18. I hereby certify that the foregoing is true and correct

SIGNED

Anna M. Shugart

TITLE Expl. & Prod. Administrator

DATE

4/24/96

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

WMOCD

ACCEPTED FOR RECORD

MAY 03 1996

FARMINGTON DISTRICT OFFICE

BY