

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Sundry Notices and Reports on Wells

1. Type of Well
GAS

2. Name of Operator

**BURLINGTON
RESOURCES**

**OIL CON. DIV.
DIST. 3
OIL & GAS COMPANY**

3. Address & Phone No. of Operator

PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M

1450' FSL, 990' FEL, Sec. 12, T-30-N, R-6-W, NMPM

1750 1085 J

5. Lease Number
SF-080713

6. If Indian, All. or
Tribe Name

7. Unit Agreement Name

San Juan 30-6 Unit
8. Well Name & Number
San Juan 30-6 U #29A
9. API Well No.
30-039-25607
10. Field and Pool
Blanco Mesaverde
11. County and State
Rio Arriba Co, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission

Type of Action

☐ Notice of Intent	☐ Abandonment	☐ Change of Plans
☒ Subsequent Report	☐ Recompletion	☐ New Construction
☐ Final Abandonment	☐ Plugging Back	☐ Non-Routine Fracturing
	☐ Casing Repair	☐ Water Shut off
	☐ Altering Casing	☐ Conversion to Injection
	☒ Other - Spud	

13. Describe Proposed or Completed Operations

12-13-96 MIRU. Spud well @ 2:00 p.m. 12-13-96. Drill to 244'. Circ hole clean. TOOH. TIH w/5 jts 9 5/8" 36# K-55 ST&C csg, set @ 235'. Cmdt w/165 sx Class "G" neat cmt w/3% calcium chloride, 0.25 pps Celloflake (195 cu.ft.). Circ 16 bbl cmt to surface. WOC. NU BOP.

12-14-96 PT BOP & csg to 600 psi/30 min, OK. Drilling ahead.

12-16-96 Drill to intermediate TD @ 3395'. Circ hole clean. TOOH. TIH w/79 jts 7" 23# C-50 LT&C csg, set @ 3389'. Cmdt w/313 sx Class "B" neat cmt w/10% calcium chloride, 20 bbl sodium silicate, 0.5 pps Flocele, 10 pps Gilsonite (901 cu.ft.). Tailed 90 sx Class "B" 50/50 poz w/2% gel, 2% calcium chloride, 10 pps Gilsonite, 0.5 pps Flocele (110 cu.ft.). Circ 41 bbl cmt to surface.

12-17-96 WOC. PT csg & BOP to 1500 psi/15 min, OK. Drilling ahead.

12-18-96 Drill to TD @ 5781'. TOOH to log.

12-19-96 TIH. Log well. TOOH. TIH w/58 jts 4 1/2" 10.5# K-55 LT&C lnr.

12-20-96 Set lnr @ 5780'. Top of lnr @ 3242'. Cmdt lnr w/155 sx Class "B" 65/35 poz w/6% gel, 0.25 pps Flocele, 5 pps Gilsonite (282 cu.ft.). Tailed w/140 sx Class "B" 50/50 poz w/0.25 pps Flocele, 5 pps Gilsonite, 0.3% fluid loss (186 cu.ft.). Reverse circ 31 bbl cmt to surface. PT lnr to 3000 psi/15 min, OK. RD. Rig released.

14. I hereby certify that the foregoing is true and correct.

Signed *Regan Brachfeld* Title Regulatory Administrator Date 1/29/97

(This space for Federal or State Office use)

APPROVED BY _____ Title _____ Date _____

CONDITION OF APPROVAL, if any:

ACCEPTED FOR RECORD

FEB 03 1996

FARMINGTON DISTRICT OFFICE

BY *[Signature]*

NMOCD