STATE OF NEW MEXICO **ENERGY and MINERALS** DEPARTMENT

OIL CONSERVATION DIVISION

Page i Revised 10/01/78

This form is not to be used for reporting packer leakage tests in Southeast New Mexico

NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

Well BURLINGTON RESOURCES OIL & GAS CO. Operator SAN JUAN 30-6 UNIT No. 114 Location of Well: С Unit Twp. Rge. 006W County RIO ARRIBA NAME OF RESERVOIR OR POOL TYPE OF PROD METHOD OF PROD. PROD. MEDIUM (Oil or Gas) (Flow or Art. Lift) (Tbg. or Csg.) Upper **MESAVERDE** Gas Flow Tubing Completion Lower DAKOTA Gas Flow Completion Tubing PRE-FLOW SHUT-IN PRESSURE DATA Upper Hour, date shut-in Length of time shut-in SI press, psig Stabilized? (Yes or No) Completion 05/25/2001 120 Hours 360 Lower Completion 05/25/2001 72 Hours 940 FLOW TEST NO. 1 Commenced at (hour.date)* 05/28/2001 Zone producing (Upper or Lower) LOWER TIME LAPSED TIME PRESSURI PROD. ZONE (hour.date) SINCE* **Upper Completion** Lower Completion TEMP REMARKS 05/29/2001 96 Hours 360 285 05/30/2001 120 Hours 368 280 Production rate during test Oil BOPD based on Grav **GOR**

Gas

MCFPD: Tested thru (Orifice or Meter):

		MID-TEST SHUT-IN PRESSURE DATA					
Upper Completion	Hour, date shut-in	Length of time shut-in	SI press. psig	Stabilized? (Yes or No)			
Lower Completion	Hour, date shut-in	Length of time shut-in	SI press. psig	Stabilized? (Yes or No)			

6446602 351

(Continue on reverse side)

FLOW TEST NO. 2

Commenced at (hour, de	ate)**		Zone producing (Upper or Lower):		
TIME	LAPSED TIME SINCE "	PRESSURE		PROD. ZONE	REMARKS
(hour, date)		Upper Completion	Lower Completion	TEMP.	REMARKS
					
					· · · · · · · · · · · · · · · · · · ·
		<u> </u>			
Production rate du	ring test				
Troduction rate do	unia icsi				
Oil:	В	OPD based on	Bbls. in	Hours	Grav GOR
Gas.		MCFF	D: Tested thru (O	rifice of Meter):	
Remarks:					
					
	-				
I hereby certify th	at the information h	erein contained is true	e and complete to	the best of my knowled	ge.
	AUG 2 4 2	NN1			
Approved			9	Operator Burling	ton Resources
New Mexico C	Dil Conservation Div	rision		B. Coloro	Place
amen	IAL GLONISTO DV ALI	AGENTAL T SPECIAL SERVICE		D. A. M. P. C. C.	~~~
By	AT 21@WED BY CH			Title Operations	A ssociate
-	DEPOTY OF &	GAS INSPECTOR, E	IST. #5		
Title				Date Friday, July	20, 2001

NORTHWEST NEWMEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- 1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- 2 At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4 For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to lack of a pipeline connection the flow period shall be three hours.
- 5. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above
- 6. Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except

that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced

7 Pressures for gas-zone tests must be measured on each zone with a deadweigh: pressure gauge at time intervals as follows. 3 hours tests immediately prior to the beginning of each flow period, at lifteen-minute intervals during the first hour thereof and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point, and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test cata.

24-hour oil zone tests, all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.

8 The results of the above-described tests shall be filed in triplicate within 15 days after—completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the floxing temperatures (gas zones only) and gravity and GOR (oil zones only)