

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.

Use "APPLICATION FOR PERMIT - " for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

ENERGEN RESOURCES CORPORATION

3. Address and Telephone No.

2198 Bloomfield Highway, Farmington, NM 87401

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1561' FNL, 946' FWL, Sec. 19, T30N, R4W, N.M.P.M.

5. Lease Designation and Serial No.

SF-079487A

6. If Indian, Allottee or Tribe Name

7. Unit or CA, Agreement Designation

8. Well Name and No.

Carson 4

9. API Well No.

30-039-25914

10. Field and Pool, or exploratory Area

Blanco MV

11. County or Parish, State

Rio Arriba NM

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☒ Other Case
☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

7/30/99 Drilled to TD of 4635'.

8/6/99 Ran 105 jts., 7", 20# & 23#, J-55 LT&C casing 4619' set at 4630'. Stage tool set at 3811'.

Cemented 1st Stage with 65/35 poz with 6% gel, 10#/sk gilsonite, 1/2#/sk flocele and 2% CaCL2 followed by 175 sks Class B 10#/sk gilsonite, 1/2#/sk flocele and 2% CaCL2 (316 cu. ft.) Plug down at 9 pm 8/5/99.

Circ. for 6 hrs. Cemented 2nd Stage with 475 sks 65/35 poz with 6% gel, 10#/sk gilsonite, 1/2#/sk flocele and 2% CaCL2 followed by 100 sks Class B, 10#/sk gilsonite, 1/2#/sk flocele and 2% CaCL2 (1046 cu. ft.)

Plug down 10 am 8/6/99. Did not circulate to surface. WOC. Run temp survey. TOC 1075' tested casing to 1200 psi - OK.

14. I hereby certify that the foregoing is true and correct

Signed

Monica Taylor

Title Production Assistant

Date 8/16/99

(This space for Federal or State office use)

Approved by

Title

Conditions of approval, if any:

ACCEPTED FOR RECORD

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

* See Instruction on Reverse Side

AMMCD

FARMINGTON FIELD OFFICE
BY *[Signature]*