

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FORM APPROVED  
Budget Bureau No. 1004-0135  
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.

Use "APPLICATION FOR PERMIT - " for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

Taurus Exploration U.S.A., Inc.

3. Address and Telephone No.

2198 Bloomfield Highway; Farmington, NM 87401

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1761' FSL, 1190' FEL, Sec. 19, T30N, R4W, NMPM

5. Lease Designation and Serial No.

SF-07947-A

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

San Juan 30-4 Unit

8. Well Name and No.

San Juan 30-4 Unit 42

9. API Well No.

10. Field and Pool, or exploratory Area

Blanco Mesaverde/Basin  
Dakota

11. County or Parish, State

Rio Arriba NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent  
☒ Subsequent Report  
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment  
☐ Recompletion  
☐ Plugging Back  
☐ Casing Repair  
☐ Altering Casing  
☒ Other Intermediate Casing  
☐ Change of Plans  
☐ New Construction  
☐ Non-Routine Fracturing  
☐ Water Shut-Off  
☐ Conversion to Injection  
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

9/17/98 Drilled to 4660'. Ran 108 joints 7 5/8 26.40#, K-55 LTC casing 4643', set at 4657'. DV tool set at 3901'. Cement 1st stage with 255 sks Class B w/ 2% CaCL2, 10#/sk gilsonite and 1/4#/sk flocele. Plug down 7:40am 9/17/98. Opened DV tool. Circ. out 12 BBL cement. Cemented 2nd stage with 1035 sks 65/35 poz with 6% gel, 2% CaCL2, 1/4#/sk flocele and 10#/sk gilsonite followed by 100 sks Class B with 2% CaCL2, 1/4#/sk flocele and 10#/sk gilsonite. (2421 cu. ft.). Plug down 12:30pm 9/17/98. Cir. 400 sks cement to surface. Tested casing to 1500 psi-OK.

14. I hereby certify that the foregoing is true and correct

Signed [Signature] Title Production Superintendent Date 9/22/98

(This space for Federal or State office use)

Approved by \_\_\_\_\_ Title \_\_\_\_\_  
Conditions of approval, if any:

ACCEPTED FOR RECORD

OCT 02 1998

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

\* See Instruction on Reverse Side

NMOC

FARMINGTON DISTRICT OFFICE  
BY [Signature]