

submitted in lieu of Form 3160-5

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Sundry Notices and Reports on Wells

1. Type of Well
GAS

2. Name of Operator

**BURLINGTON
RESOURCES**

OIL & GAS COMPANY

3. Address & Phone No. of Operator

PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M

1800' FNL, 1520' FEL, Sec. 28, T-30-N, R-6-W, NMPM

5. Lease Number

SF-080712A

6. If Indian, All. or
Tribe Name

7. Unit Agreement Name

San Juan 30-6 Unit

8. Well Name & Number

San Juan 30-6 U #130

9. API Well No.

30-039-26216

10. Field and Pool

WC:30N5W28G Pict.Cliffs

11. County and State

Rio Arriba Co, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission

☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment

Type of Action

☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☒ Altering Casing
☐ Other -
☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut off
☐ Conversion to Injection

13. Describe Proposed or Completed Operations

- 11-15-99 Drill to 3700'. Circ hole clean. TOOH. TIH, ran logs. TOOH. TIH w/coring tools. Cut sidewall cores @ 3167, 3175, 3189, 3203, 3212, 3219, 3225, 3261, 3265, 3269, 3273, 3281, 3295, 3302, 3307, 3311'. TOOH. TIH, cut sidewall cores @ 3346, 3358, 3366, 3373, 3391, 3431, 3473, 3539' for 24 cores total. TOOH. TIH w/7 7/8" bit. Drilling ahead.
- 11-16-99 Drill to TD @ 3725'. Circ hole clean. TIH w/82 jts 4 1/2" 10.5# J-55 ST&C csg, set @ 3721'. Pump 5 bbl wtr, 10 bbl chemical wash, 10 bbl zone lock, 5 bbl wtr ahead. Cmt d w/300 sx Class "B" neat cmt w/2% sodium metasilicate, 7 pps Kolite, 0.5 pps Flocele, 0.1% retardant, 0.1% dispersant (513 cu.ft.). DV tool was open. Circ 90 bbl cmt to surface. TOOH w/4 1/2" csg.
- 11-17-99 TIH w/7 7/8" bit to 2715'. Establish circ. TIH to 3200'. Wash down csg. Circ hole clean. TOOH. TIH w/82 jts 4 1/2" 10.5# J-55 ST&C csg, set @ 3703'. Circ hole clean.
- 11-18-99 Pump 5 bbl wtr, 10 bbl calcium chloride, 10 bbl wtr, 10 bbl zone lock, 5 bbl wtr ahead. Cmt d w/559 sx Class "B" neat cmt w/7 pps Kolite, 0.5 pps Flocele, 0.1% retardant, 3% sodium metasilicate (1627 cu.ft.). Tailed w/201 sx Litecret w/0.15% retardant, 0.11% fluid loss, 0.45% D-65, 0.03% foamer, 8.32 pps D-164, 38.76 pps extender (420 cu.ft.). Displace w/59 bbl wtr. Circ 113 bbl cmt to surface. WOC. PT csg to 3800 psi/15 min, OK. ND BOP. NU WH. RD. Rig released.

14. I hereby certify that the foregoing is true and correct.

Signed Deann Cole Title Regulatory Administrator Date 11/29/99
no

(This space for Federal or State Office use)

APPROVED BY _____ Title _____ Date _____

CONDITION OF APPROVAL, if any:

ACCEPTED FOR RECORD

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

NMOC

DEC 01 1999
FARMINGTON FIELD OFFICE
BY