Form 3160-5 (August 1999)

UNITED STATES DEPARTMENT OF THE INTERIOR **BUREAU OF LAND MANAGEMENT**

FORM APPROVED OMB NO. 1004-0135 Expires: November 30, 2000

	Serial	NT.	

•

٥.	Lease	Serial	Νo
SF-	0805	38	

SUNDRY	NOTICES	and	REPORTS	ON	WELLS	
Do not use this form for proposals to drill or to re-enter an						

	r proposals to drill or to re-ent rm 3160-3 (APD) for such pro		1970	6. If Indian, Allo	ttee or Tribe Name	
SUBMIT IN TRIPLICATE -	Other instructions on re	verse side ///	4 3	7. If Unit or CA/	Agreement, Name and/or No.	
1. Type of Well		To Park	3000	San Juan 30	-5 Unit	
Oil Well X Gas Well Other		Control of the contro		8. Well Name an		
2. Name of Operator		Vi Con	97 3	4	11440	
Phillips Petroleum Company		6.3		SJ 30-5 Unit	#113	
3a. Address	3b.	Phone No. Cinclude as	rea gode	30-039-26360	5	
5525 Highway 64, NBU 3004, Farmingt		05-599-3454 & 7	Jan Barrell		ol, or Exploratory Area	
4. Location of Well (Footage, Sec., T., R., M., or Surve	y Description)			Basin Dakota		
Unit K, 1474' FSL & 1781' FWL				Blanco Mesay		
Section 11, T30N, R5W				11. County or Pa	-	
				<u> Rio Arriba.</u>	NM	
12. CHECK APPROPRI	ATE BOX(ES) TO INDICA	ATE NATURE OF NO	OTICE, REPORT	, OR OTHER DAT.	<u>A</u>	
TYPE OF SUBMISSION		TYF	PE OF ACTION			
Notice of Intent	Acidize	Deepen	Production	n (Start/Resume)	Water Shut-Off	
	Alter Casing	Fracture Treat	Reclamati	on	Well Integrity	
X Subsequent Report	Casing Repair	New Construction	Recomple	te D	Other 4-1/2"	
	Change Flans	Plug and Abandon		ily Abandon		
Final Abandonment Notice		= -		· -	casing report	
	Convert to Injection	Plug Back	Water Dis	posar		
RIH w/6-1/4" bit & tagged cement 4017'. Drilled ahead to 8190, TD. 8194' - 4015'. Ran 4-1/2" 11.6% stage. Pumped lead - 250 sx (426 bbl slurry) Class H cement w/1/4% w/126.2 bbls FW. Set ECP & openerslurry) premium lite. Tail - 50 fluid to surface. Plug down @ 91 ND BOP & set slips & cut off 4-1/PT on next report.	@ 3950'. PT casin TD reached 6/16/ casing & set @ 81 5.7 cf - 76 bbl slu sx Cello-flake, 5 ed DV tool @ 750 ps sx (73 cf - 13 bbl 4 hrs w/1250 psi.	00. Circ. COOH 89', ECP - 5856 rry) premium li #/sx Gilsonite, i. Pumped 2nd s slurry) Type Held good. WC	I. Ran CNL, I. & DV too te cement. 0.3% FL-25 Stage lead 3 w/1/4#/sx	CAL, Temp. ol 5848'. RU Tail - 50 sx o, Dropped pl - 115 sx (24 c Cello-flake	LDT, AIT, from to cement 1st (70 cf -12.5 ug & displaced 1 cf - 43 bbls , 1% CaCl2. No	
 I hereby certify that the foregoing is true and correct Name (Printed Typed) 	_	Title				
	Patsy Clugston		Sr. Regula	tory/Prorati		
Jala Clugat		Date 6/2	21/00	ACCEPTE	FOR RECORL	
THIS SPACE FOR FEDERAL OR STATE OFFICE USE						
Approved by		Title		Julia	ו מ בטטט =	
Conditions of approval, if any, are attached. Approval certify that the applicant holds legal or equitable title to which would entitle the applicant to conduct operations thereon	those rights in the subject			FARMING I	UN FIELD OFFICE	
Title 18 U.S.C. Section 1001, and Title 43 U.S.C. Section States any false, fictitious or fraudulent statements or represent	on 1212, makes it a crime for tations as to any matter within it	any person knowingly s jurisdiction.	and willfully to r	nake to any departm	ent or agency of the United	