

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM-014387

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

H.J. Loe "B" FEDERAL

9. WELL NO.

2

10. FIELD AND POOL, OR WILDCAT

Basin Dakota

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

23-T29N-R12W

12. COUNTY OR PARISH

13. STATE

San Juan

N. Mex.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)1. OIL ☐ WELL GAS ☒ WELL OTHER

2. NAME OF OPERATOR

TEXACO, Inc.

3. ADDRESS OF OPERATOR

P.O. Box EE, Cortez, Colo. 81321

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

1850' from North line and 2310' from East line.

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

5668' DF

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

Plug back of well

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones perti-
nent to this work.)*

Commenced plug back to 3122' on 2-4-77 as follows:

1. Ran tubing to 4500'.
2. Pumped in 120 sx. of class B cement. WOC
3. Tagged cement top at 3626'.
4. Set Model N CIBP at 3204'.
5. Perforated at 3190' with four way shot.
6. Ran tubing and packer and set at 3075'.
7. Squeezed perfs with 50 sx. class B cement and shut in
with 500 psi. WOC
8. Tagged cement top at 3122'.



18. I hereby certify that the foregoing is true and correct

SIGNED

Alvin R. Marx

TITLE

Field Foreman

DATE

2-7-1977

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

USGS(4) NMOCC(3) JAS-GLE-ARM-JHP