

X			

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Budget Bureau No. 42-R358.4.
Form Approved.

Land Office Santa Fe
Lease No. 079947-A
Unit 1/2 Section 34

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL		SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF		SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL		SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE		SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING		SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL	X		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)


Simmons "D"

Farmington, New Mexico November 5, 1963

Well No. 1 is located 1190 ft. from NE line and 1090 ft. from W line of sec. 34

SW/4 SW/4 Section 34 T-29N R-9W N.M.P.M.
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)

Blanco Mesaverte San Juan New Mexico
(Field) (County or Subdivision) (State or Territory)



The elevation of the derrick floor above sea level is 5807 ft. (RGS)

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudlogging, cementing points, and all other important proposed work)

This refers to our "Notice of Intention to Abandon Well" dated 10/21/63. We propose to abandon the subject well by one of the two below listed procedures:

1. Pump 200 sacks cement down casing to fill open hole section 3776 to 4672. Top of cement will be left at about 3700 (7" casing set at 3776).
2. Fill 7" casing with heavy fluid and spot 5 sacks cement surface plug 0-20'.
3. Pump 50 sacks cement in 9-5/8" - 7" casing annulus (9-5/8" set at 150').

OR

2. Cut off 7" casing at free point and pull all salvagable casing.
3. Spot cement plugs as follows: 100' plug on top of 7" casing stub, 200' plug over Pictured Cliffs - Fruitland formations (if above 7" casing stub), 100'

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

(SEE REV. 34 SIDE)

Company PAN AMERICAN PETROLEUM CORPORATION

Fred L. Nabors, District Engineer

Address P. O. Box 400

Farmington, New Mexico

ORIGINAL SIGNED BY
F. H. HOLLINGSWORTH

By

Title

1. 5. Plug over Ojo Alamo formation and 5 sacks cement surface plug 0-24'.
6. Pump 50 sacks cement in 8 1/2" casing annulus (9-1/2" set at 150').
7. 5. Reset abandonment marker and clean up location.