

(SUBMIT IN TRIPLICATE)

Indian Agency Window Rock, Ariz.

Navajo

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Allottee Navajo Tract #23

Lease No. 14-20-603-5025

Sec. 36	
T29N R15W	

SUNDRY NOTICES AND REPORTS ON WELLS

RECEIVED

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF	JUL 19 1963
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING	U. S. GEOLOGICAL SURVEY
NOTICE OF INTENTION TO REDRILL OR REPAIR WELL	SUBSEQUENT REPORT OF REDRILLING OR REPAIR	FARMINGTON, NEW MEXICO
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL	<u>Subsequent Report for Squeezing</u>	
	<u>Lost Circulation Zone</u>	<u>X</u>

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

July 10, 1963

Well No. 1 is located 1980 ft. from [N] line and 1980 ft. from [E] line of sec. 36

NW 36, Sec. 36
(1/4 Sec. and Sec. No.)

29N
(Twp.)

15W
(Range)

NMPM
(Meridian)

Pajarito Area
(Field)

San Juan
(County or Subdivision)

New Mexico
(State or Territory)

The elevation of the derrick floor above sea level is 5247 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

7/8/63 - Squeezed lost circulation zone in open hole below 7" csg. @ 6196' to 6403', w/100 sacks reg. cement w/12.5% Gilsenite per sack. Pumped 6 bbls. mud, 5-3/4 bbls. per min., pumping rate 1500# press, 14.4# slurry. Displaced cement w/53 bbls. mud. Left 48' cement in btm. of 7" csg., standing press. 200#. Drilled 309' of firm cement, started losing returns @ 6449'. Trip out of hole to squeeze lost circulation zone @ 6196' to 6449'.

7/9/63 Squeezed lost circulation zone in open hole below 7" csg. @ 6196' to 6449', w/100 sacks reg. cement w/12.5% Gilsenite per sack. Pumped in 5 bbls. @ 5 bbls. per min., pumping rate @ 1400# press.. 14.4# Slurry. Displaced w/53 bbls. mud. Left 27' of cement in btm. of 7" csg., Max. press. 1200#, standing press. 300#. Drilled 380' firm cement, lost circulation @ 6457', no returns. On trip out of hole to squeeze lost circulation zone @ 6196' to 6457'.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Amerada Petroleum Corporation

Address Box 1469

Durango, Colorado

247-5353

By E. Holbrook

Title Foram



