


Form 9-331a
(Feb. 1951)

(SUBMIT IN TRIPLICATE)

Land Office Santa Fe
Lease No. SF 080247
Unit 1/2 Sec. 25



UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	<input checked="" type="checkbox"/>	SUBSEQUENT REPORT OF WATER SHUT-OFF.....	
NOTICE OF INTENTION TO CHANGE PLANS.....		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....		SUBSEQUENT REPORT OF ALTERING CASING.....	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....		SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.....	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....		SUBSEQUENT REPORT OF ABANDONMENT.....	
NOTICE OF INTENTION TO PULL OR ALTER CASING.....		SUPPLEMENTARY WELL HISTORY.....	
NOTICE OF INTENTION TO ABANDON WELL.....			

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

January 23, 1956

Floresce
Well No. 86 is located 990 ft. from S line and 990 ft. from W line of sec. 25

SW 1/4 Sec. 25 29N 9E 14PM
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)

Blanco (Manzanita) San Juan New Mexico
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 5920 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

We propose to drill with rotary tools using mud to base of Pictured Cliffs (approx. 2500'). Set intermediate casing and drill with gas to base of Dakota (approx. 7150') and set production string of casing, perforate the Dakota, Point Lookout, Manatee, and the Cliff House, sand water fracturing each of the above formations for dual completion thru the Dakota and Man Vanda Sections.

PROPOSED CASING PROGRAM

200' of 13 3/8" 48# 11-40 SS Casing - Cemented to Surface
2500' of 9 5/8" 36# 11-40 SS Casing - Cemented with 200 sacks
7150' of 7" 20#, 23#, and 280 SS Casing - Cemented with 500 sacks
7100' of 2 1/2" 6.50# 1-55 Tubing (w/ packer at approx. 5000')

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Bulhi-Taylor Oil Corporation

Address P. O. Box 1175

Farmington, New Mexico

By J. M. Howell

Title Dist. Supt.