

212

5709 GL

7-13-71

1545

12-13-51

3-1-52

1558

1520

1520

1520

1520

1520

1520

1520

1520

F. Loc. 1650/S; 990/E

Casing S. 8-5/8 @ 102 w 100 Sx. Int. @ W Sx. Pr. 5 1/2 @ 1500 W 125 Sx. T. 1 @ 1510

Csg. Perf. 1500-20

Prod. Stim. 1 cone shot. 1496-1510

Closed Area 1506-1523 OH

8-6-71

11-4-53

1st Del.

Grav.

Days GOR

PSI After 3

Hrs. SICIP 460

TOPS

NIID

C-103

C-104

Diir

Dair 2-24-71

Doc 3-17-72

General M. words 4ip.

7-12-71 12-11-71 11-11-71 11-11-71

This well has the same casing

As being as before, & was cleaned

up by circulating of them

acid to be used.

permeability

W. M. Galloway

Tenneco O Co.

Bay Petr.

160

W. Kutz PC Co. SJ s 27 t 29N r 13W u. Oper. Coleman Oil & Gas Co. Lse. G. H. Callow No. 1

Sched.	10	9	8	7	6	5
54	391	108	144	196	96	
9/16/55	289	64	186	145	79	
5/8/56	267	41	197	132	63	
7/8/57	277	23	223	138	44	
7/25/58	283	22	199	141	31	
7/6/59	267	15	222	133	32	
6/6/60	252	9	225	126	27	
5/9/65	267	7	182	214	5	
6/6/66	240	4	209	192	5	
7/2/67	283	6	214	226	5	
6/3/68	190	4	165	152	6	
Discontinued			7-1-69		#1630	